

Part # GISB-E-36-54-18

GRATE -




Flow Specifications Total Percent Square Flow Description Open Square Inches Rate of filter Inches of Total (Cubic opening per Unit Unobstructed Feet per Openings Second) Skimmer protected By-Pass 100% 15.0cfs 384.4 384.4 Coarse Screen 3/4" \times 1-3/4" stainless steel 62% 328.1 203.4 9.2cfs flattened expanded Medium Screen 10x10 mesh 56% 328.1 183.7 9.4 cfs stainless steel Fine screen 14 x 18 mesh 68% 249.4 169.6 9.2cfs stainless steel THROAT FLOW RATE TREATED FLOW RATE Total:37.6 cfs Total: 27.8 cfs FLOW RATES BASED ON UNOBSTRUCTED OPENINGS





SIDE VIEW



BOX MANUFACTURED FROM MARINE GRADE FIBERGLASS & GEL COATED FOR UV PROTECTION

5 YEAR MANUFACTURERS WARRANTY

PATENTED

ALL FILTER SCREENS ARE STAINLESS STEEL

SUNTREE QUALITY PRODUCTS ARE BUILT FOR EASY CLEANING AND ARE DESIGNED TO BE PERMANENT INFRASTRUCTURE AND SHOULD LAST FOR DECADES.

4		4 .4
△¶		4 4
4		
4	$23\frac{1}{2}$	<i>A</i>
4 4.4	END VIEW	A A
4	CONCRETE STRUCTURE	4

MOUNT TO WALL BELOW
GRATE WITH MOUNTING KIT
CONSISTING OF ALUMINUM
ANGLES, TAPCONS, AND DRILL BITS
MOUNTING KIT
SOLD SEPARATELY

SUNTREE TECHNOLOGIES	PROJECTI		
COCOA FL. 32922	REVISIONS:	DATE	
TEL. 321-637-7552 FAX 321-637-7554	REVISIONS	DATE	
GRATE INLET SKIMMER BOX FOR			
FLORIDA DOT TYPE E INLET STRUCTURES.	REVISIONS	DATE:	
DATE: 04/12/04 SCALE:SF = 20	REVISIONS	DATE:	
DRAFTER: N.R.B. UNITS =INCHES	REVISIONS:	DATE	