


30
SPECIFICATION

For industrial toilet installations. Designed to secure toilet to waste piping connection and floor

DESIGN FEATURES

- Cast Iron Top Ring and base ring with corrosion resistant coating
- Instant Set® drain pipe attachment. No additional hardware required
- Stainless steel fasteners
- Models with test cap eliminate the need for additional drain pipe sealing caps for inspection

COMPLIANCES/LISTINGS

- Compliant to PS-97 standards listed in IAPMO File: 793
- Compliant to Uniform Plumbing Code (UPC®)
- Compliant to International Plumbing Code (IPC®)



3689 Arrowhead Drive, Carson City, NV 89706
 Phone (800) 854-3215 Fax (800) 243-1777
 E-mail sales@lspproducts.com Website www.lspproducts.com

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained.

CLOSET FLANGES

30, 30TC, 40, 40TC, 40TCSL 44, 46, OS40

Specification Sheet

| Part Number | Description |
|-------------------|---|
| 30 | 3" x 2" Closet Ring |
| 30TC | 3" x 2" Closet Ring w/ Test Cap |
| 40 | 4" x 2" Closet Ring |
| 40TC | 4" x 2" Closet Ring w/ Test Cap |
| 40TCSL | 4" x 2" Slotted Closet Ring w/ Test Cap |
| 44 | 4" x 4" Deep Closet Ring |
| 46 | 4" x 6" Deep Closet Ring |
| OS40 | 4" x 2" Closet Ring 3/4 Offset |
| Replacement Parts | |
| 300-022-3 | 3" Seal Gasket |
| 300-022-3TC | 3" Seal Gasket with Test |
| 300-022-4 | 4" Seal Gasket |
| 300-022-4TC | 4" Seal Gasket with Test |
| ICR-008 | 1/4"-20 X 1-1/4" SS Bolt |
| ICR-015 | 1/4"-20 X 1-1/2" SS Bolt (OS40 only) |
| ICR-030 | 1/4"-20 X 2-1/2" SS Bolt (44 only) |
| ICR-003-6 | 1/4"-20 X 14" SS Bolt (46 only) |
| WR-ICR | Stainless Steel Flat Washer |


40TCSL


| Product Submittal | |
|-------------------|----------|
| Job Name: | |
| Date: | |
| Part Number | Quantity |
| | |
| | |
| Architect: | |
| Contractor: | |




Frank Pattern

DIMENSIONS

Top View




Side View



CLOSET FLANGES
30, 30TC, 40, 40TC, 40TCSL, 44, 46, OS40
 Specification Sheet

INSTALLATION

1. Position Frank Pattern closet flange assembly over drain pipe and secure to floor with appropriate size flat head screws
2. Instant Set closet rings clamp on outside of drain pipe
3. Evenly tighten bolts (E) evenly until drain is secure, 20 in-lbs., max.
4. After Leak Testing drain system, cut-out exposed rubber seal using utility knife. Models with test cap only
5. Install Toilet per manufactures instructions



| Part Number | Nominal Drain Pipe Size | Drain Connection | Dimensions (Inches) | | | |
|-------------|-------------------------|------------------|---------------------|---------|---------|-------|
| | | | A | B | C | D |
| 30 | 3" | Instant Set | 4-5/8 | 2-1/4 | 6-7/8 | 5-3/4 |
| 30TC | 3" | Instant Set | 4-5/8 | 2-1/4 | 6-7/8 | 5-3/4 |
| 40 | 4" | Instant Set | 5-1/2 | 2-1/16 | 7-1/16 | 5-5/8 |
| 40TC | 4" | Instant Set | 5-1/2 | 1-7/8 | 7-1/16 | 5-5/8 |
| 40TCSL | 4" | Instant Set | 5-1/2 | 1-7/8 | 7-1/16 | 6" |
| 44 | 4" | Instant Set | 5-1/2 | 3-7/16 | 7 | 5-1/2 |
| 46 | 4" | Instant Set | 5-1/2 | 4-13/16 | 7 | 5-1/2 |
| *OS40 | 4" | Instant Set | 5-1/2 | 2-1/8 | 7-11/16 | 5-3/4 |



3689 Arrowhead Drive, Carson City, NV 89706
 Phone (800) 854-3215 Fax (800) 243-1777
 E-mail sales@lspproducts.com Website www.lspproducts.com
 Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained.

| Product Submittal | |
|-------------------|----------|
| Job Name: | |
| Date: | |
| Part Number | Quantity |
| | |
| | |
| Architect: | |
| Contractor: | |