

## NLCBC-45 COBALT Series - 4" 95 CRI Recessed Retrofit Downlight

Source: 16.6W Chip on Board 1000Lm LED

### PRODUCT DESCRIPTION

Nora Lighting's 4" LED Cobalt Luminaires are cULus listed for use in existing 4" IC or Non-IC housings manufactured by Nora and others. The units provide 1000 Lumen output, drawing 16.6W and rendering 95CRI. Nora's 4" Cobalt LEDs integrate the latest from the Cree® COB family of LED arrays, giving bright spectacular light output and low power consumption. An obvious and smart choice for Green Energy efficient lighting in commercial and residential applications.

### FEATURES

- 5 year limited warranty
- CREE® COB LED
- Dimmable
- cULus Listed, Energy Star & Title 24 compliant
- 1000lm utilizes only 16.6W
- Available in 2700K, 3000K and 4000K color temperature, 95 CRI
- GU24 Socket adapter available for use with GU24 base housings- Includes Medium-Base Socket kit

### CONSTRUCTION

**Trim:** Aluminum spun reflector (NLCBC-451) with deep set diffused lens for excellent visual comfort while providing high lumen output.

Aluminum spun baffle trim (NLCBC-452) with deep set diffused lens and deep grooves to reduce aperture glare while providing high lumen output.

**Lens:** Shatter proof diffused poly carbonate lens.

**Deep Trim:** The deep trim places the LED optics deeper than the standard increasing the visual comfort. Additionally the deep cones reduces board images when off.

### RETROFIT

Cobalt Series Downlights include NRA-211 Medium Base screw-in socket for retrofitting into existing Medium Base downlight housings.

### ELECTRICAL SYSTEM

**Voltage:** 120VAC

**Current:** 270mA

**Power Consumption:** 16.6 Watts

**Light Source:** Cree COB

**Lumens:** 1000 lm

**CRI:** 95 CRI

**LED Driver:** Built-in driver

**Operating Temperature:** 0°C to 75°C ambient temperature

**Life Expectancy:** 50,000 hours



NRA-211 Medium Base screw-in socket  
Included with every Cobalt Series for retrofitting into existing Medium Base Downlight Housings

### DIMMABLE

Nora LED Cobalt Series works with standard leading and trailing edge dimming technologies. Dimming with trailing-edge dimmers (electronic) are 5-100% and for leading-edge dimmers (incandescent) 10-100%. There may be some cases that require more than one lighting fixture to be used to meet minimum dimmer load. Consult with dimmer manufacturer. [Click Here](#) or refer to [www.NoraLighting.com](#) for complete updated dimmer list in the "Compatibility" page under the "Resource" tab.

### 4" Cobalt 95CRI Retrofit/Premium Deep Recessed Downlight

Catalog No.	Color Temp.	Finish	Option
NLCBC-451	27 = 2700K	Retrofit Recessed	EM = Pre-Wired for EM use
NLCBC-452	30 = 3000K	WW = White	with EM housing
NLCBC-451D	40 = 4000K	Premium Deep Recessed	
NLCBC-452D		BZ = Bronze	
		DW* = Diffused Clear / White	
		HZW* = Haze / White	
		WW = White	
NLCBC-451	30 = 3000K	WW = White	LE4 = 120V Triac / 120V or 277V
	35 = 3500K	DW = Diffused Clear/White	0-10V Dimming <sup>2</sup>
		DD = Diffused Clear /Diffused	LE4EM = 120V Triac / 120V or 277V 0-10V Dimming and EM <sup>4</sup>

\*Finish only available on Reflector Style


1 - Requires 277V Input supply

2 - Compatible with NHIC-6LMRAT/4W & NHIC-6LMRAT/4W housing

3 - Compatible with NHIC-6LMRAT/EM housing

4 - Compatible with NHIC-6LMRAT/6WEM

### DIMENSIONS



### LABELS & LISTINGS

cULus Listed  
Title 24 Compliant  
Energy Star Rated



CREE 5 YEAR LEDs Limited Warranty

### COMPATIBLE HOUSINGS

#### FireBox

NFBIC-4LMRAT 4" ICAT Dedicated LED 2-Hour Fire Rated

#### New Construction

- NSIC-401QAT 4" ICAT Line Voltage
- NS-401QAT 4" AT Line Voltage
- NHIC-4G24AT 4" ICAT GU24 (Specify NRA-212 adaptor separately)
- NHIC-4LMRAT 4" ICAT Dedicated LED
- NHIC-4LMRAT/277 4" ICAT Dedicated LED, 277V
- NHIC-4LMRAT/4W 4" IC Air Tight Dedicated Housing Pre-wired for 0-10V dimming Cobalt Series
- NHIC-4LMRAT/EM 4" IC Air Tight Dedicated Housing Pre-wired for Emergency Cobalt Series - Includes EM battery and remote test switch
- NHIC-4LMRAT/6WEM 4" IC Air Tight Dedicated Housing Pre-wired for Emergency and 0-10V dimming Cobalt Series - Includes EM battery and remote test switch

#### Remodel

- NSR-404QAT 4" AT Line Voltage
- NHRIC-4G24AT 4" ICAT GU24 (Specify NRA-212 adaptor separately)
- NHRIC-4LMRAT 4" ICAT Dedicated LED
- NHRIC-4LMRAT/4W 4" IC Air Tight Remodel Housing Pre-wired for 0-10V dimming Cobalt Series

Create a complete Item number: Example: NLCBC-45127WW 4" Cobalt with Smooth White Reflector and flange - 2700K.