

Class 300 Stainless Steel Flanged Ball Valves

Split-Body, Full-Bore Design • Blowout-Proof Stem • 316 SS Trim •
Mounting Pad • Fire Safe • Vented Ball

720 PSI/50 bar non-shock cold working pressure*

CONFORMS TO ASME/ANSI B16.34, B16.5, MSS SP 72,
API 607 FOURTH EDITION, API 608, API 598,
MSS SP 25

MATERIAL LIST

PART	SPECIFICATION
1. Body and End Piece	Stainless Steel ASTM A 351 Type CF8M
2. ¹ Ball (Vented)	Stainless Steel ASTM A 351 Type CF8M
3. Stem	Stainless Steel ASTM A 276 Type 316
4. Seat	Carbon Filled PTFE
5. Packing Set	Graphite and Braided Graphite
6. Pack Gland	Stainless Steel ASTM A 276 Type 316
7. Gasket	304 SS/Graphite Spiral Wound
8. Body Stud	Stainless Steel ASTM A 193 Grade B8 SS
9. Heavy Hex Body Nut	Stainless Steel ASTM A 194 Grade 8 SS
10. Belleville Washer	Stainless Steel

¹Cast specifications shown. Smaller sizes may be manufactured from equivalent bar stock specifications.


DIMENSIONS—WEIGHTS—QUANTITIES

		Dimensions									
Size		A	B	C	D	E					
In.	mm.	In.	mm.	In.	mm.	In.	mm.	In.	mm.	In.	mm.
½	15	5.50	140	3.14	80	.56	14	3.75	95	.59	15
¾	20	6.00	152	3.43	81	.62	16	4.63	118	.78	20
1	25	6.50	165	3.55	90	.69	18	4.88	124	.98	25
1½	40	7.50	191	4.13	105	.81	21	6.13	156	1.57	40
2	50	8.50	216	4.74	120	.88	22	6.50	165	2.00	51
3	80	11.12	253	5.56	141	1.12	28	8.25	210	3.00	76
4	100	12.00	305	6.01	156	1.25	32	10.00	254	4.00	102
6	150	15.87	403	7.96	202	1.44	37	12.50	318	6.00	152
8	200	19.75	502	9.87	251	1.62	41	15.00	381	8.00	203
10	250	22.38	569	11.19	234	1.88	48	17.50	445	10.08	256
12	300	25.50	649	12.75	324	2.00	51	20.50	521	12.09	307

		Dimensions											
Size		G	H	J	K	L		O	*P	Q	R	F-535-S6-F-66-FS	
In.	mm.	In.	mm.	In.	mm.	In.	mm.	In.	mm.	In.	mm.	Lbs.	Kg.
½	15	5.12	130	3.52	89	.34	9	1.00	25	.19	5	250-20	—
¾	20	6.10	155	4.13	105	.43	11	1.26	32	.31	8	250-20	—
1	25	6.10	155	4.25	108	.45	11	1.26	32	.31	8	.312-18	—
1½	40	9.06	230	4.97	126	.92	23	1.68	43	.47	12	.312-18	—
2	50	9.06	230	5.66	144	1.58	40	1.66	42	.63	16	.312-18	—
3	80	15.75	400	7.38	187	2.26	57	2.13	54	.78	20	.375-16	4.13
4	100	15.75	400	8.09	205	2.10	53	2.13	54	.78	20	.437-14	4.13
6	150	—	—	—	—	2.93	74	2.58	66	1.10	28	.437-14	4.96
8	200	—	—	—	—	4.43	113	2.53	65	1.17	30	.500-13	4.96
10	250	—	—	—	—	5.08	129	3.01	76	1.57	40	.625-11	5.90
12	300	—	—	—	—	4.97	126	3.01	76	1.57	40	.625-11	5.90


*Not drilled and tapped on ½"-2". Note: valves are static grounded by thrust washer.

◆For detailed operating pressure, refer to pressure temperature chart on page 86.





F-535-S6-F-66-FS


Stainless x Stainless
Flanged



½"-8"



10"-12"



Visit our website for the most current information.