



010 Fiber Coat Liquid Asphalt Coating

- Great for Coating Worn Roofs
- Damp-Proofs Foundation Walls
- Liquid Brush Grade

Gardner® Fiber Coat is a liquid applied, brushable, asphalt based coating designed to protect worn roof surfaces. When applied across the entire roof surface, it provides weatherproofing protection from the elements. Also great choice for damp-proofing foundation walls below grade.

PREPARATION: Surfaces must be clean, free of surface rust and loose material.

APPLICATION: Use roof brush and wear gloves, to spread across surface of roof. Apply on a clear warm day with no rain expected for 24 hours. Apply when surface temperatures are between 50 °F and 120 °F. This product is formulated to be used year round. In colder weather (50 °F and below), product should be stored in heated room 70 °F to 80 °F, at least 24 hours prior to application to promote ease of application. **MIXING MAY BE REQUIRED TO ENSURE PRODUCT UNIFORMITY. DO NOT APPLY DIRECT HEAT/FLAMES OR THIN.** Allow product to cure a minimum of 30 - 60 days prior to application of a reflective coating.

COVERAGE RATE: Covers approximately 50 sq. ft. per gallon.

PRECAUTIONS: For exterior use only. Protective clothing and eyewear should be used during application of this product. Use with adequate ventilation. Don't apply to wet surfaces. Do not use on EPDM, TPO, PVC or other rubber/synthetic surfaces. If there is a question on compatibility, test a small section first. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100 °F. This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not reuse empty containers. Do not use in drinking water or food systems. Seal container when not in use. Protect from freezing.

CLEAN-UP: Clean tools or spills with paint thinner or mineral spirits.

WARRANTY AND DISCLAIMER: Gardner-Gibson, Inc. warrants this product to give satisfactory results when our directions are followed in its use and application, for a period of 12 months from the date of purchase. In no event however shall the manufacturer be liable for an amount in excess of the purchase price of the product used. If not completely satisfied, return to place of purchase for a refund.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
0101-GA	1 gal.	6.75" x 6.75" x 7.75"	3.6 qt. / 3.4 L	8 lbs.	6/case	025056010100
0105-GA	5 gal.	12" x 12" x 14.75"	4.75 gal / 18 L	40 lbs.	1 ea.	025056010506

www.gardner-gibson.com
Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449
Phone: (813) 248-2101