

ProPEX brass female threaded adapters

Submittal information

Date submitted:

Project Information


Job name :	Location :
Engineer :	Date submitted:
Contractor :	Submitted by:
Manufacturer's representative :	Approved by :

Technical Data

Material	Brass
Temp./pressure ratings	73°F (23°C) at 160 psi (11 bar) 180°F (82°C) at 100 psi (6.9 bar) 200°F (93°C) at 80 psi (5.5 bar)

Product information and application use

ProPEX® brass female threaded adapters connect Uponor PEX pipe to female NPT threads. Use the adapters in hydronic heating and cooling systems. One end of the adapter is manufactured with the Uponor ProPEX fitting for connection to Wirsbo hePEX™ pipe; the other end is manufactured to adapt a male thread. These adapters are not safe for direct burial in soil. Note: Not for potable use.



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	Cv	Weight per UOM [lbs/UOM]	Equivalent length through [ft]	End type 1
ProPEX Brass Female Threaded Adapter, 5/8" PEX x 3/4" NPT	Q4576375	1.906	1.04	1.345	0.486	0.866	1.187	-	0.2	-	ProPEX 5/8"
ProPEX Brass Female Threaded Adapter, 1" PEX x 1" NPT	Q5571010	2.381	1.2	1.717	0.52	1.181	1.5	19.7	0.4	3.8	ProPEX 1"
ProPEX Brass Female Threaded Adapter, 1 1/4" PEX x 1 1/4" NPT	Q5571313	2.57	1.125	2.294	0.415	1.445	2.0	30.8	0.67	4.8	ProPEX 1-1/4"
ProPEX Brass Female Threaded Adapter, 1 1/2" PEX x 1 1/2" NPT	Q5571515	2.854	1.15	2.583	0.42	1.704	2.25	40.9	1.2	5.1	ProPEX 1-1/2"
ProPEX Brass Female Threaded Adapter, 2" PEX x 2" NPT	Q5572020	3.547	1.4	3.449	0.703	2.147	3.0	77.7	2.2	5.7	ProPEX 2"
ProPEX Brass Female Threaded Adapter, 1/2" PEX x 1/2" NPT	Q5575050	1.569	0.86	1.139	0.326	0.709	1.0	4.8	0.14	2.5	ProPEX 1/2"
ProPEX Brass Female Threaded Adapter, 3/4" PEX x 1" NPT	Q5577510	2.145	1.2	1.717	0.52	0.945	1.5	10.8	0.4	3.6	ProPEX 3/4"
ProPEX Brass Female Threaded Adapter, 3/4" PEX x 3/4" NPT	Q5577575	1.845	0.9	1.356	0.347	0.945	1.187	12	0.2	2.3	ProPEX 3/4"

Part name	Part no.	End type 2
ProPEX Brass Female Threaded Adapter, 5/8" PEX x 3/4" NPT	Q4576375	FNPT 3/4"
ProPEX Brass Female Threaded Adapter, 1" PEX x 1" NPT	Q5571010	FNPT 1"
ProPEX Brass Female Threaded Adapter, 1 1/4" PEX x 1 1/4" NPT	Q5571313	FNPT 1-1/4"
ProPEX Brass Female Threaded Adapter, 1 1/2" PEX x 1 1/2" NPT	Q5571515	FNPT 1-1/2"
ProPEX Brass Female Threaded Adapter, 2" PEX x 2" NPT	Q5572020	FNPT 2"
ProPEX Brass Female Threaded Adapter, 1/2" PEX x 1/2" NPT	Q5575050	FNPT 1/2"
ProPEX Brass Female Threaded Adapter, 3/4" PEX x 1" NPT	Q5577510	FNPT 1"
ProPEX Brass Female Threaded Adapter, 3/4" PEX x 3/4" NPT	Q5577575	FNPT 3/4"

Installation		Related applications	
Use the appropriate ProPEX ring for Uponor PEX pipe (sold separately). Refer to the Uponor Radiant Installation Handbook, Complete Design Assistance Manual (CDAM), or Hydronic Piping Design Assistance Manual (HPDAM) for additional information.		Radiant Heating and Cooling Systems	
		Permafrost Protection Systems	
		Turf Conditioning Systems	
		Hydronic Piping Systems	
Codes	Standards	Listings	
IMC IBC IRC NPC of Canada UMC	ASTM F1960 CSA B137.5 NSF-14 ASTM F877	IAPMO-ES ICC-ES-PMG cNSFus-rfh	
Trademark Information		Contact information	
ProPEX® is a registered trademark of Uponor Inc. ProPEX™ is a trademark of Uponor Ltd.		Uponor Inc.	
		5925 148th Street West	
		Apple Valley, MN 55124	
		T 800.321.4739	
		F 952.891.2008	
		Uponor Ltd.	
		6510 Kennedy Road	
		Mississauga, ON L5T 2X4	
		T 888.594.7726	
		F 800.636.9517	