




**AC CABLE DUPLEX CONNECTORS**

90° Squeeze Connectors, Uninsulated Die Cast Zinc  
N/A

**B69.1**



Catalog #: 2691

**APPLICATIONS**

- For use in dry locations to bond flexible metal conduit to a box or enclosure
- N/A
- For use in dry locations to bond armored cable to a box or enclosure

**PRODUCT FEATURES**

Rugged metallic construction insures mechanical protection for the raceway

**UL LISTED**

Standard 514B, File E195969

**CSA**

C22.2 No. 18

**GENERAL PRODUCT INFORMATION**

Trade Size: 3/8 in.

**DRAWING DIMENSIONS**

- Dimension A: 25/64 in.
- Dimension B: 1-25/32 in.
- Dimension C: 29/64 in. - 25/32 in.
- Dimension D: NO. 8x1/2 in.
- Dimension E: 1/2 in. - 14 NPSM

**PACKAGING**

- Package Type: Carton
- Std. Pkg.: 50
- Ship Carton Qty.: 500
- Product UPC-A Labeled: No
- Weight (Lbs. Per/C): 8.80
- Ship Carton Length (in.): 19.00
- Ship Carton Width (in.): 10.95
- Ship Carton Height (in.): 8.00
- Ctn Weight (Lbs.): 44.00
- UPC Number: 050169026915
- I2of5: 50050169026910