

**SOURAVIT** 





Mirror cabinet (recessed version)	Dimension	Weight	Order number
cEGS/IAPMO®*, LED lighting (4-sided), 3 mirror doors, 4 glass shelves (clear glass), back panel inside mirror glass, GFCI outlets are not supplied by the manufacturer (GFCI outlets can be added to the cabinet by a certified electrician on the job site) LED dimming function, LED (life span > 30,000 hours), LED module permanently enclosed, Mirrors cabinets require a GFCI 110 V 60 Hz power source and are hardwired to a circuit provided by the customer. , LED module 3500 kelvin light color 52 Watt			
Colors			
Variant			
	47 1/4" x 6 1/8" Inch		LC7653
Infobox			
# LC 7653 is available from stock, On/off and dimming function 9688 or external wall switch, Recess frame # LC 9688 is mand as a separate line item, Built-in frame optional, * Complies with 1982	atory for installation and	is required to be ordered	
Suitable products			
Recess frame Aluminum White, frame width 1", height 29 1/2", 49 1/4" x 3/8" Inch	49 1/4" x 3/8" Inch		LC9898
Magnetic strip in stainless steel , 3 1/2" Inch	3 1/2" Inch		UV9709

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.