

- Available in LED, Incandescent, & GU24
- Molded of Durable Non-Corrosive UV Resistant Resins
- Wall Mount Only
- UL Listed for Wet Locations
- Standard Pack QTY: 6

FITTER NECK POCKET



EXAMPLE # FP103-LE800C-BCP

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FP103 FP106 FP109	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70* AMBIENT OP TEMP -40°C (-40°F) TO +50°C (122°F) 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR LE800 - 13W Power Input CRI 80 (TYP) >65 Lumens Per Watt** W -900lm 3000K C -1000lm 4000K	W -White B - Black	ACRYLIC C -Clear Prism W -White	P -Photocell
	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C (-40°F) TO +40°C (105°F), 3 YEAR WARRANTY L900 - 11.3W Power Input CRI 74 (TYP) >80 Lumens Per Watt** W -White B - Black	W -White B - Black	ACRYLIC C -Clear Prism W -White	
	INCANDESCENT, MEDIUM BASE, 120V ENERGY STAR WITH LAMP OPTION I60 -1 X 60W	W -White B - Black	POLYCARBONATE C -Clear Prism W -White	P -Photocell LSW -9W, 2700K, LED Lamp LSC -9W, 4000K, LED Lamp
	GU24 BASE, 120V, ENERGY STAR WITH LAMP OPTION G13 -1 X 13W G18 -1 X 18W G23 -1 X 23W	W -White B - Black	ACRYLIC C -Clear Prism W -White	P -Photocell L -2700K, CFL



Scan the QR code to the left to access the Energy Star qualified product list.