

Specialty Products™



DESIGN FEATURES

- Easy to Install
- Size AA, ASSE 1010 Certified.
- No access panel or maintenance required
- May be installed at any angle
- Patented inline Hammer Arrestor eliminates water hammer
- Exceeds all ASTM A112.18.6 Flow requirements
- Is effective when installed in any direction

MATERIAL SPECIFICATIONS

- P-06406 meets ASTM F2159, F876, AND F877
- P-06407 meets ASTM F1960, F876, AND F877
- P-06408 meets ASTM D2846

OPERATING SPECIFICATIONS

- Temperature: 40-160°F
- Max working pressure 125 PSI

CAUTION

- Keep PEX versions Away from Solvents/Cements/Primers
- Keep out of constant direct sunlight
- For Indoor Use Only



3689 Arrowhead Drive, Carson City, NV 89706
 Phone (800) 854-3215 Fax (800) 243-1777
 E-mail sales@lspproducts.com Website
 www.lspproducts.com

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained. (Rev C 6-16)

POLYMER MINI INLINE HAMMER ARRESTER Specification Sheet

Part Number	Description
P-06406	1/2" Crimp PEX x 1/2" Crimp PEX
P-06407	1/2" Uponor PEX x 1/2" Uponor PEX
P-06408	1/2" Male CPVC x 1/2" Male CPVC

COMPLIANCES/LISTINGS

- IAPMO listed to Lead Free Plumbing Law, File 6545
- IAPMO listed to ASSE 1010, File 4541
- IAPMO listed to NSF/ANSI 61, File N-6614 OR
- NSF International listed to NSF/ANSI 61



NSF/ANSI 61
ASSE 1010



Lead Free Compliant

INSTALLATION INSTRUCTION

1. Can be installed in any direction, but preferred installation is with water flow in direction of arrow
2. Install according to piping manufacturing installation instructions
3. After installation, check for leaks

Product Submittal	
Job Name:	
Date:	
Part Number	Quantity
Architect:	
Contractor:	