

POLYMER MINI INLINE HAMMER ARRESTOR

DESIGN FEATURES

- Easy to Install
- Size AA, ASSE 1010 Certified.
- No access panel or maintenance required
- May be installed at any angle
- Patented inline Hammer Arrestor eliminates water hammer
- Exceeds all ASTM A112.18.6 Flow requirements
- Is effective when installed in any direction

MATERIAL SPECIFICATIONS

- P-06406 meets ASTM F2159, F876, AND F877
- P-06407 meets ASTM F1960, F876, AND F877
- P-06408 meets ASTM D2846

OPERATING SPECIFICATIONS

- Temperature: 30-180°F
- Max working pressure 150 PSI

CAUTION

- Keep PEX versions Away from Solvents/Cements/Primers
- Keep out of constant direct sunlight
- For Indoor Use Only

COMPLIANCES/LISTINGS

- IAPMO listed to Lead Free Plumbing Law, File 6545
- IAPMO listed to ASSE 1010, File 4541
- IAPMO listed to NSF/ANSI 61, File N-6614 OR
- NSF International listed to NSF/ANSI 61



ASSE 1010



Part Number	Description	MSTR CTN QTY
P-06406	1/2" Crimp PEX	50
P-06407	1/2" UPONOR ProPEX®	50
P-06408	1/2" Male CPVC	50

INSTALLATION INSTRUCTIONS

1. Can be installed in any direction, but preferred in-stallation is with water flow in direction of arrow
2. Install according to piping manufacturing installation instructions
3. After installation, check for leaks

Product Submittal	
Job Name:	Date:
Part Number:	Quantity:
Architect:	
Contractor:	

Content matter is subject to change at any time. It is the user's responsibility to ensure the most updated revisions are obtained. Rev C 7/2022