SFERGUSON FACILITIES SUPPLY



FEATURES

- Energy Savings of up to 87% •
- Lumen Maintenance over 70% @ 50,000+ Hours •
- No UV/IR Radiation, No Toxic Mercury •
- **Brushed Nickel Steel Pan** •
- Die Formed of 22 Gauge Plated Steel •
- Replaces 2 x 60W Incandescent •
- Dimmable .

OPTICS

Alabaster-Style Glass •

APPLICATIONS

- Hallways .
- Bedrooms
- Bathrooms •
- Lobbies

CERTIFICATIONS

- UL/cUL Listed •
- **Energy Star**
- **Lighting Facts**

SPECIFICATIONS

Part Number: <u>LED1101B-35</u>			
Limited Manufacturer Warranty:	3 Years	Certifications:	UL Listed
Kelvin Temperature (CCT):	2700K	DLC Listed:	No
Wattage:	15.09W	Average Hour Life:	50,000 hrs
Lumens:	1209 lm	Max. Amblent Temperature:	45°C
Efficacy:	80.12 lm/w	Min. Amblent Temperature:	-20°C
CRI:	80	Power Factor:	>0.9
Dimmable:	0-10V Dimming	THD:	<20%
Input Voltage:	DC 120V		
TECHNICAL			
Weight:	3.72 lbs	Product Width:	11.5"
Length:	11.5"	LED Beam Angel:	120
Product Height:	3.5"	LED Type:	Integrated LED Array









FACILITIES SUPPLY

LINE DRAWINGS





LIGHTING FACTS

Cordelia Lighting

Lighting facts®

Light Output (Lumens)	1209
Watts	15.09
Lumens per Watt (Efficacy)	80.12
Color Accuracy Color Rendering Index (CRI)	81

Light Color Correlated Color T	emperature (CCT)	2700 (Warm White)		
Warm White	Bright White	Day	light	
	DOK	4500K	6500	

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: ZMBK-3XAFBC (1/17/2017) Model Number: LED1101B-## Type: Luminaire - Downlight