LUCÉ

WALL

Boasting an elegant slice of sleek stainless steel married with the subtle glamor of ambient lighting in Cloud White, Deep Blue and Amber, the Lucé is the (gorgeous) future of range hoods, here today. Featuring ACTTM

technology, BriteStrip $^{\text{TM}}$ LED lighting, ICON Touch $^{\text{®}}$ Controls and a versatile Recirculating Option.





ACT


	INTERNAL BLOWER STANDARD	INTERNAL BLOWER with ACT™ AIRFLOW CONTROL TECHNOLOGY™*				
Min Max. CFM	200 - 600	200 - 390	200 - 290			
Min Max. Sones	Ain Max. Sones 1 - 6		1 - 3			

*AIRFLOW CONTROL TECHNOLOGY $^{\text{TM}}$ (ACT $^{\text{TM}}$) is an exclusive feature built into specific Zephyr hoods which can limit the maximum blower CFM to meet local code requirements.











MODEL Stainless Steel w/ Accent Lighting	ZLU-E30BS	ZLU-M90BS
Size	20//	2//
Blower CFM (Min Max.)	30" 200 - 600	36" 200 - 600
Sones (Min Max.)	1 - 6	1 - 6
ACT 390 CFM (Min Max.)	200 - 390	200 - 390
ACT 390 Sones (Min Max.)	1 - 4	1 - 4
ACT 290 CFM (Min Max.)	200 - 290	200 - 290
ACT 290 Sones (Min Max.)	1 - 3	1 - 3
FEATURES		
ACT™ Technology	Yes	Yes
Controls	ICON Touch®	ICON Touch®
Speed Levels	5*	5*
Auto Delay-Off	Yes	Yes
Lighting	BriteStrip™ LED x1	BriteStrip™ LED x1
Dual-Level Lighting	Yes	Yes
LED Accent Light	Yes; Cloud White, Deep	Yes; Cloud White, Deep
	Blue & Amber	Blue & Amber
Filters	Aluminum Mesh x2	Aluminum Mesh x2
Recirculating Option	Yes	Yes
Extension Duct Cover Option	Yes, Up to 12' Ceiling	Yes, Up to 12' Ceiling
DUCT SPECIFICATIONS		
Vertical Internal Blower	6" Round	6" Round
Horizontal Internal Blower	NA	NA
AC POWER	120V, 60Hz at Max. 3A	120V, 60Hz at Max. 3A
OPTIONAL ACCESSORIES		
Recirculating Kit	ZRC-00LU	ZRC-00LU
Extension Duct Cover	Z1C-00LU	Z1C-00LU
Make-Up Air Kit	MUA006A	MUA006A
MOUNTING HEIGHT RANGE**	26" - 34"	26" - 34"
WARRANTY	3 years parts, 1 year labor	3 years parts, 1 year labor

CEILING HEIGHT		8′	8.5′	9'	9.5′	10′	10.5′	11'	12'
STANDARD DUCT COVER	Ducted Mounting Height**	26" - 33.5"	26" - 34"	26" - 34"	28" - 34"	34" - 34"	NA	NA	NA
	Recirc Mounting Height**	26" - 29"	26" - 34"	26" - 34"	28" - 34"	34" - 34"	NA	NA	NA
EXTENSION DUCT COVER	Ducted Mounting Height**	NA	NA	26" - 30.5"	26" - 34"	26" - 34"	26" - 34"	26" - 34"	28" - 34"
	Recirc Mounting Height**	NA	NA	26" - 26.5"	26" - 32.5"	26" - 34"	26" - 34"	26" - 34"	28" - 34"

^{*}When ACT ** is enabled the maximum speed levels will change. ACT 390 CFM = 3 speeds and ACT 290 CFM = 2 speeds.
**Mounting height refers to distance between top of a 36" tall cooking surface and bottom of hood.



AIRFLOW CONTROL TECHNOLOGY™ (ACT™) is an exclusive feature built into specific Zephyr hoods which can limit the maximum blower CFM to meet local code requirements.

