

# One-light Led Pendant

 Ceiling mounted • Damp location listed **PROGRESS LED**


## Description:

The one-light 12" pendant features industrial roots in both form and function. The Polished Chrome finish highlight the high-quality prismatic glass which adds to the historical aesthetic. Antique style fixture includes a hinge-locking nautical design. Perfect above a kitchen island in pairs or threes, use for additional ambience or task lighting in, breakfast nooks, islands, offices, and dining rooms or anywhere a pendant light can be placed. 3000k, 90+ CRI 1,211 lumens 71.2 lumens/watt per module (source).

## Specifications:

- Polished Chrome (-15) (plated)
- Steel Construction
- Clear Fresnel glass lens
- LED Module is replaceable (part # 93053641)
- Antique inspired with industrial roots
- Includes two 6", one 12", two 15" stems and 6 links of chain.
- Dimmable to 10% with many ELV dimmers
- 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 10 feet of wire supplied
- Two 6", one 12", two 15" lengths of stem included
- Six links of 9 gauge chain supplied
- ENERGY STAR® qualified

## Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1211/71.2 (LM-82)
Lumens/LPW (Delivered)	987/57.1 (LM-79)
CCT	3000 K
CRI	90+
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

## P5188-1530K9

## Images:



## Dimensions:

Diameter: 12-1/8"  
 Height: 10-1/2"  
 Overall Ht. W/Stem: 76-1/2"

Glass  
 Width: 10-1/16"  
 Length: 10-1/16"  
 Height: 1"

## P5188-1530K9

### Dimming Notes:

---

P5188 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

### Dimming Controls

---

Lutron Nova T NTELV-300

Lutron Vienti VTELV-600

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.