



SLING HARDWARE

Swivel Eye Rigging Hooks

- Pre-drilled for latches.
- Heat-treated, quenched and tempered.
- Design factor 5:1.



	¹ Rated Cap.* (tons)	Part Number	Dimensions (in.)												Wgt. Ea. (lbs.)
			A	B	C	D	G	H	I	L	R	S	T	O	
DOMESTIC	1	1ASWH	2.00	1.11	1.31	3.06	0.87	1.05	0.63	5.83	4.63	0.38	0.87	0.93	1.05
	1-1/2	112ASWH	2.50	1.38	1.50	3.33	0.94	1.11	0.71	6.83	5.44	0.50	0.97	0.97	1.56
	2	2ASWH	3.00	1.65	1.75	3.67	1.06	1.21	0.88	7.76	6.25	0.63	1.03	1.06	2.50
	3	3ASWH	3.00	1.65	1.75	4.20	1.27	1.43	0.94	8.40	6.49	0.63	1.16	1.16	3.20
	5	5ASWH	3.50	1.77	2.00	5.11	1.44	1.63	1.31	9.76	7.53	0.75	1.53	1.41	5.36
	7	7ASWH	4.75	2.39	2.75	6.24	1.82	2.01	1.68	12.42	9.67	1.00	1.94	1.69	10.56
	11	11ASWH	5.50	2.55	3.25	7.69	2.25	2.63	1.88	14.89	12.06	1.13	2.46	2.22	19.00
	15	15ASWH	6.00	2.47	3.50	8.37	2.59	2.94	2.19	15.79	11.95	1.25	2.62	2.23	26.75
	22	22ASWH	7.75	3.82	4.75	10.19	3.00	3.50	2.69	21.18	16.68	1.50	2.74	3.05	51.80

Latches are not included on domestic hooks. If latches are required, you must specify when ordering.


Part Number	1ASWH	112ASWH	2ASWH	3ASWH	5ASWH	7ASWH	11ASWH	15ASWH	22ASWH
Latch Kit	1LK	112LK	2LK	3LK	5LK	7LK	11LK	15LK	22LK

	¹ Rated Capacity* (tons)	Part Number	Dimensions (in.)					
			B	C	O	R	S	T
IMPORT	1-1/2	112ASWHLI	1.31	1.50	0.97	5.28	0.50	0.81
	2	2ASWHLI	1.63	1.75	1.00	6.02	0.63	0.84
	3	3ASWHLI	1.56	1.75	1.13	6.38	0.63	1.19
	4-1/2	5ASWHLI	1.75	2.00	1.34	7.41	0.75	1.38
	7	7ASWHLI	2.31	2.50	1.69	9.59	1.00	1.78
	11	11ASWHLI	2.38	2.75	2.06	11.13	1.13	2.13
	15	15ASWHLI	2.81	3.13	2.25	11.94	1.25	2.50

¹ Rated Capacity also referred to as Working Load Limit.


Import

- Alloy steel
- Used on wire rope and synthetic slings and Lift-All's GripHook.



Sorting Hooks

- Quenched and tempered alloy steel.
- Long tapered point designed for easy grab in rings, pear links, eye bolts or lifting holes.
- Durable powder-coated finish.
- Do not load last 1" of the tip.
- Design factor 5:1.



Part Number*	Dimensions (in.)										Wgt. (lbs.)
	A	B	C	D	E	F	G	H	I	M	
2SORT	3.00	1.44	0.78	7.34	3.75	1.28	1.25	3.93	10.09	6.58	6.8

* For Handle, add H to part number (2SORTH).

WLL at tip: **2.0-Ton**
WLL at bowl: **7.5-Ton**

WARNING Do not exceed rated capacities. Sling capacity decreases as the angle from horizontal decreases. Do not use slings at angles of less than 30°. Refer to the Effect of Angle chart found in the General Information section of this catalog.