

SeeSnake® Wi-Fi Enabled Monitors and Recorders



RIDGID® SEESNAKE CS6X DIGITAL RECORDING MONITOR

With a lightweight body and small form factor, the CS6x is designed for portability and convenience. Quickly capture and share inspection photos and videos right from the job site. Dock the CS6x onto a SeeSnake Max™ rM200 reel for easy transport.

FEATURES

- Built-in Wi-Fi and Bluetooth allows live inspection streaming on an iOS or Android device with the free HQx® Live app.
- Capture photos, PhotoTalk™ media, video, and Autolog directly to a USB drive
- Compatible with all SeeSnake camera reels.
- TiltSense™ displays the camera's degree of tilt from horizontal when connected to a SeeSnake camera reel with TruSense™.
- Water-resistant keypad gives direct control of camera and monitor functions.
- Daylight viewable display provides a crisp, clear, in-pipe image.

SPECIFICATIONS

- Length – 14.2" (362 mm)
- Width – 6.5" (165 mm)
- Height – 5.1" (130 mm)
- Display – 5.7" (145 mm) Color LCD
- Display Resolution – 640 x 480 (VGA)
- Power Source – 18 V Advanced Lithium Battery or AC adapter
- Operating Temperature – 14°F to 122°F (-10°C to 50°C)
- Storage Temperature – 14°F to 158°F (-10°C to 70°C)
- Media Transfer – USB Drive or Wi-Fi via HQx Live
- Audio – Integrated Microphone and Speakers
- Autolog Format – MPEG4 (H.264)
- Photo Format – JPEG
- Video Format – MPEG4 (H.264)



SeeSnake rM200 with CS6x used as a monitor and recording device

Catalog No.	Description	Weight	
		lb	kg
56803	CS6x Digital Recording Monitor	3.4	1.6
57138	CS6x w/2 Batteries and 1 Charger	7.4	3.4
45363	AC Battery Adapter	1	0.5
44693	18 V Advanced Lithium 2.0 Ah Battery	1	0.5
44698	18 V Advanced Lithium 4.0 Ah Battery	1.5	0.7
43458	18 V Advanced Lithium Battery Charger	1.8	0.8

