



PRODUCT SUBMITTAL 249

Product: PRO-BALANCE® White Surface Mount Heating Manifold Cabinets

Date: 19 January 2018 (supersedes 13 September 2016)





	Typical	Frame/Cabinet Opening		Outside Cabinet Dimensions		
	Station	Α	B*	W	Н	D
Article No.	Configuration	in (cm)	in (cm)	in (cm)	in (cm)	in (cm)
		16	19	19.7	28.7	5.1
347400-512	up to 3	(43)	(49)	(50.0)	(73.0)	(13)
	•	20	19	23.8	28.7	5.1
347410-512	up to 5	(53)	(49)	(60.5)	(73.0)	(13)
	•	28	19	31.7	28.7	5.1
347420-512	up to 8	(73)	(49)	(80.5)	(73.0)	(13)
	•	36	19	39.6	28.7	5.1
347430-512	up to 11	(93)	(49)	(10.1)	(73.0)	(13)
		44	19	47.4	28.7	5.1
347440-512	up to 12	(113)	(49)	(12.1)	(73.0)	(13)
		50	19	53.3	28.7	5.1
347450-512	up to 12	(128)	(49)	(13.5)	(73.0)	(13)

For updates to this publication, visit na.rehau.com/resourcecenter

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained therefrom. Before using, the user will determine suitability of the information for user's intended use and shall assume all risk and liability in connection therewith.

www.rehau.com PS249, 19-Jan-18, Page 1 of 2

TECHNICAL DESCRIPTION

Material 20 gauge, galvanized steel with basic white powder coat finish (RAL 9016 / Pantone 705)

FUNCTIONAL DESCRIPTION

PRO-BALANCE manifold cabinets for surface installation. The cabinets are made from 20 gauge galvanized steel with basic white powder coat finish (RAL 9016 / Pantone 705). Internal brackets allow for easy mounting of PRO-BALANCE 1 and 1 1/4 in. brass manifolds. Cabinet steel door comes with white slotted cabinet lock(s). Accessory item sold separately is the keyed cabinet lock (Art. 217688-001) which replaces an existing slotted cabinet lock.

Installation Note: manifold cabinet should be installed before manifold, screed and thermal mass

*Removable coverplate below door temporarily extends cabinet opening to the floor (27 in / 69 cm).







Coverplate and door removed

Door removed

Fully assembled cabinet

ACCESSORIES

The following PRO-BALANCE manifold cabinet accessories are sold separately:



PRO-BALANCE Brass Manifold Cabinet Lock

Manifold keyed cabinet lock used to replace the pre-installed slotted cabinet lock on both the flush mount and the surface mount cabinets. Lock comes with two keys.

Article No.	Description	Mounting Hole
217688-001	Keyed Lock for 34XXXX cabinets	19 mm square