


- LG1-1TBC Finish(C)
- LG1-1TBD Finish(D)
- LG1-1TBK Finish(K)
- LG1-1TBY Finish(Y)

- LG1-2TBC Finish(C)
- LG1-2TBD Finish(D)
- LG1-2TBK Finish(K)
- LG1-2TBY Finish(Y)
- LG1-3TBC Finish(C)
- LG1-3TBD Finish(D)
- LG1-3TBK Finish(K)
- LG1-3TBY Finish(Y)



Specifications

- All Metal Construction
- High Arc Spout

Features

- 1.8 GPM Flow Rate (Handheld Shower)
- 60" Metal Hose
- All Metal Construction
- Adjustable Heights
- Adjustable Install
- Easy To Clean Nozzles
- High Arc Spout
- Laminar Water Flow
- SecurePfit™
- Pforever Warranty®

Code Compliance

Pfister products are designed and manufactured in compliance with the following standards and codes:

- IAPMO Certified
- CSA B125 Certified
- ASME A112.18.1
- NSF 61/9 Annex G (Low lead)
- Cal Green Compliant
- CEC Compliant
- EPA WaterSense Certification 1.8 gpm, 6.8 L/Min
- ADA Compliant-ANSI A117.1 (Lever handles only)



Dimensions

