utility

SUMP

sewage

well

l lawn

pool

specialty

submersible

CORROSION RESISTANT STAINLESS <

- High Performance; 3/4 HP Pumps Up To 5673 GPH @ 0'
- Integrated Vertical Float Switch with Solid, Leak Free Polypropylene Float for Automatic Operation; 9 in. ON Level and 4 in. OFF Level
- No Need for Weep Holes; Unique Top Suction Design Reduces Clogging and Prevents Air Lock Condition
- Designed For Easy Installation Without Any Plumbing Changes
- Engineered with Upper and Lower Ball Bearings, in Sealed Oil Bath, for Virtually Silent Operation
- 1-1/2 in. NPT Discharge for Compliance with Building Codes
- Easy Carry Handle For Portability
- Float Guard Protects Switch From Hang-Ups from Debris and Side of Pit






		PERFORMANCE									
Ī	Model	HP	Discharge Head	5'	10'	15'	20'				
	CDU980E	3/4	Gallons/Hour	5245	4743	4240	3571				

SPECIFICATIONS										
Model	HP	UPC	L	w	Н	LBS				
CDU980E	3/4	040066214744	8 (in.)	8 (in.)	12 (in.)	22				







Customer Service: 1-800-237-0987 Web Site: www.waynepumps.com