

Rely™ 60"x42" Shower Base K-8659

GREENGUARD PRODUCT CETHILD COST LOCK OFFICER LICCOM/OG ULCOM/OG ULCOM/OG

Features

- Center drain.
- Low-threshold assures ease of exit and entry of the shower space.
- Water containment bead along the step over threshold provides optimum barrier to eliminate water escaping from the shower.
- Textured bottom surface.
- One-piece construction.
- Compliments traditional and contemporary bathroom designs.
- Coordinates with Choreograph™ walls.

Material

Acrylic

Installation

- Alcove
- 3-side integral flange.



Codes/Standards

CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 Greenguard UL 2818 - Gold

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes


Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
146	G9	Sandbar





Rely™ 60"x42" Shower Base K-8659



Technical Information

All product dimensions are nominal.

Installation:
3-Wall Alcove

Drain location: Center

Weight: 73 lbs (33.1 kg)
Minimum flat for door: 2-5/8" (67 mm)
Threshold height: 3" (77 mm)

Notes

Measure your actual product for rough-in details. Install this product according to the installation instructions.

Subfloor must be within 1/2" (13 mm) of level. This receptor has a front lip. This should be taken into account when installing a shower door.

