

**Browse Catalog**

Ballasts And  
Lighting Controls

Compact  
Fluorescent

Display/Optic  
Specialty

Fluorescent

High Intensity  
Discharge (HID)

Incandescent

Lampholders/Sockets

LED Systems

Consumer  
Lifestyle  
Solutions

Miniature &  
Automotive

Starters

Halogen

LED Lamps &  
Retrofits

[Return to Search](#) [Print Page](#)



**Product Number:** 47735

**Order Abbreviation:** M175/MULTI-KIT

**General Description:** 120/208/240/277V multi-tap magnetic core and coil ballast for 175W metal halide lamp

**Product Information**

Abbrev. With Packaging Info.	M175MULTIKIT 1/CS 1/SKU
ANSI Code	M57
Ballast Factor	1
Ballast Height H (in)	5.4350
Ballast Length L (in)	7.1000
Ballast Width W (in)	7.1000
Capacitor Height	3 15/16"
Circuit Type	CWA
Input Current (Amps)	0.00
Nominal Voltage (V)	120/208/240/277V
Number of Lamps	1
Open Circuit Voltage (V)	305
Power Factor	>0.9
Primary Lamp Type	M175
Sound Rating	N
Starting Method	OCV
Starting Temperature - Fahrenheit	-22°F
Starting Temperature - Celsius	-30°C
Total Harmonic Distortion (THD)	<20%
Wiring Method	LEADS
Total Maximum Wattage	210

**Additional Product Information**

[Product Documents, Graphs, and Images](#)

[Packaging Information](#)

[Compatible Products](#) (if applicable)



**Footnotes**

- Product is a kit containing the core & coil, capacitor, ignitor (where required), brackets and mounting hardware
- Install in accordance with National Electric Codes
- Ground Ballast Core and Metallic Case of Capacitor and Ignitor
- Minimum starting temperature: -20 F / -29 C
- Product contains installation instructions

[Email](#) [Bookmark](#) [Print Page](#)