

Job Name:	
System Reference:	Date:



GENERAL FEATURES

- Square edge, sleek design
- 3D turbo fan enabling increased airflow
- Built-in 3D i-see Sensor®*
- Improved installation features*
- Occupancy detection*
- Energy saving features*
- Improved occupant comfort
- Four fan speed settings including auto-fan
- Corner pocket design for simplified installation
- Built-in condensate lift mechanism designed to provide up to 33-7/16" of lift
- Ventilation air intake supported

*3D i-See sensor® settings requires either:

PAR-40MAAU or PAR-CT01MAU-SB controller

ACCESSORIES

- ☐ Air Outlet Shutter Plate (3 pieces) (PAC-SJ37SP-E)
- ☐ High Efficiency Filter (PAC-SH59KF-E)
- ☐ Multi Function Casement (PAC-SJ41TM-E)
- ☐ Wireless Signal Receiver (PAR-SR4LU-E)
- ☐ CN24 Relay Kit (CN24RELAY-KIT-CM3)
- ☐ Wireless Remote Controller (PAR-SL100A-E)
- ☐ MaxiBlue Advanced Blue Diamond Mini Condensate Pump w/ Reservoir & Sensor (208/230V) up to 48,000 BTU/H [recommended] (X87-721 - 208/230V)

SPECIFICATIONS

Capacity*

Cooling	Btu/h	30,000
Heating	Btu/h	34,000

* Cooling / Heating capacity indicated at the maximum value at operation under the following conditions:

Cooling | Indoor: 80° F (26.7° C) DB / 67° F (19° C) WB; Outdoor 95° F (35° C) DB

Heating | Indoor: 70° F (21.1° C) DB; Outdoor 47° F (8.3° C) DB / 43° F (6° C) WB

Electrical

Electrical Power Requirements	1-phase, 208 / 230V, 60Hz	
Minimum Circuit Ampacity (MCA)	A	0.57
Recommended Fuse Size	A	15

External Dimensions (H x W x D)

Unit	In.(mm)	11-3/4 × 33-3/32 × 33-3/32 (298 × 840 × 840)
Grill (PLP-41EAEU)	In.(mm)	1-9/16 × 37-13/32 × 37-13/32 (40 × 950 × 950)

Net Weight

Unit	Lbs (kg)	55 (25)
Grill (PLP-41EAEU)	Lbs (kg)	11 (5)

External Finish

Unit	Galvanized steel sheet
Grill (PLP-41EAEU)	White - MUNSELL (6.4Y 8.9/0.4)

Coil Type

Coil Type	Cross fin
-----------	-----------

Fan

Type x Quantity	Turbo fan x 1	
Airflow Rate (Low-Mid2-Mid1-High)	CFM	636 - 706 - 777 - 812
Motor Type	DC motor	
Motor Output	kW	0.12
Motor F.L.A.	A	0.45

Air Filter

Air Filter	PP honeycomb (long life filter, anti-bacterial type)
------------	---

Refrigerant Piping Diameter

Liquid (High Pressure)	In.(mm)	3/8 (9.52) Flare
Gas (Low Pressure)	In.(mm)	5/8 (15.88) Flare

Field Drain Pipe Size


Field Drain Pipe Size	In.(mm)	O.D. 1-1/4 (32)
-----------------------	---------	-----------------

Sound Pressure Level

Low-Mid2-Mid1-High	dB(A)	28 - 31 - 33 - 35
--------------------	-------	-------------------

Model: PLFY-EP30NEMU-E – DIMENSIONS

Unit: in (mm)



◎CAPACITY OF EACH MODEL AS FOLLOWING
PLFY-EPNEMU-E: 06/08/12/15/24/30/36/48
PLFY-EPNEMU-E1: 18

PUMP/ITEM NO.	①	②	A	B	C	D	E	F
06-15	REFRIGERANT PIPES 3/8"	REFRIGERANT PIPES 1/2"	9/12	13/16			07/16 MORE	
	FLARED CONNECTION 1/4"	FLARED CONNECTION 1/2"	(241)	(258)	3/16	3/16	137/323/3500	
							OR LESS	
18			11/16	11/16			1/2000	
	REFRIGERANT PIPES 3/8"	REFRIGERANT PIPES 1/2"	(241)	(268)	3/16	3/16	177/324/3500	
	FLARED CONNECTION 1/4"	FLARED CONNECTION 1/2"					OR LESS	
24-48			29/32	29/32			07/16 MORE	

1340 Satellite Boulevard. Suwanee, GA 30024
Toll Free: 800-433-4822 www.mehvac.com



Form# PLFY-EP30NEMU-E - 202011

Specifications are subject to change without notice.

© 2020 Mitsubishi Electric Trane HVAC US, LLC