

Series 10RN
Ring Tite Joint IPS Gate Valve with Operating Nut

- 250 lb. non-shock cold working pressure
- Ductile iron body and bonnet
- Stainless steel non-rising stem
- Wax encapsulated cap screws
- Fusion bonded epoxy coating
- Meets AWWA C515
- IPS pipe size



Size IN	Part Number	Weight LB
	Push On	
2	017110RN020	27
2-1/2	017110RN025	38
3	017110RN030	47
4	017110RN040	69
6	017110RN060	146
8	017110RN080	208

Series 10NW & 10NN
ISP Threaded Gate Valve with Hand Wheel or Operating Nut

- 250 lb. non-shock cold working pressure
- Ductile iron body and bonnet
- Stainless steel non-rising stem
- Wax encapsulated cap screws
- Fusion bonded epoxy coating
- Meets AWWA C515



Size IN	Part Number		Weight LB
	Hand Wheel	Op Nut	
2	017110NW020	017110NN020	24
3	017110NW030	017110NN030	49
4	017110NW040	017110NN040	68

Series 20FC
Flanged Cast Iron Swing Check Valve

- 200 lb. cold water working pressure
- Meets AWWA C508
- Gray Iron ASTM A126, Class B Body
- Meets MSS-SP-71
- Fusion bonded epoxy coating ANSI/AWWA C550
- Flanged connection
- Resilient disc brass seat
- 4 boss design



Size IN	Part Number	Weight LB
	Flanged	
2	017320FC020	30
2-1/2	017320FC025	41
3	017320FC030	39
4	017320FC040	83
6	017320FC060	141
8	017320FC080	278
10	017320FC100	452
12	017320FC120	608

Series 20FCW
Flanged Cast Iron Swing Check Valve with Lever and Weight

- 200 lb. cold water working pressure
- Meets AWWA C508
- Gray Iron ASTM A126, Class B Body
- Meets MSS-SP-71
- Fusion bonded epoxy coating ANSI/AWWA C550
- Flanged connection
- Resilient disc brass seat
- 4 boss design



Size IN	Part Number	Weight LB
	Flanged	
2	017320FCW020	42
2-1/2	017320FCW025	45
3	017320FCW030	58
4	017320FCW040	108
6	017320FCW060	154
8	017320FCW080	314
10	017320FCW100	368
12	017320FCW120	546

Spring Kits Available