



Buy it for looks. Buy it for life.®

**DESCRIPTION**

- Chrome plated metal construction
- Pressure balancing cycle valve design with an adjustable temperature limit stop
- 1/2" IPS/CC connections
- Includes valve, tub spout, showerhead, arm and flange
- Lever and optional knob handle included

**OPERATION**

- Lever style handle
- Handle operates counterclockwise through a 270° arc with off at 6 o'clock and maximum hot at the 9 o'clock position. Shut off in clockwise direction
- Adjustable temperature limit stop to control maximum hot water temperature
- Pressure balancing mechanism maintains selected discharge temperature to ± 2°

**FLOW**

- Showerhead is limited to 1.75 gpm (6.6 L/min)

**CARTRIDGE**

- 1222 cartridge design
- Nonmetallic/nonferrous and stainless steel materials
- Accommodates back to back installations

**STANDARDS**

- Third party certified to meet ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein
- Compliant with California water efficiency regulations

- **ADA** for lever handle

- Meets Watersense® criteria
- Meets New York City Law No. 57

**WARRANTY**

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
  - 10 year limited warranty when used in a multifamily installation
  - 5 year limited warranty when used in a commercial installation
- Visit [www.moen.com/support](http://www.moen.com/support) for complete details and limitations

# Specifications



**Adler™  
POSI-TEMP®  
Single-Handle  
Tub/Shower Valve**

- Models:** 82603 Series (tub/shower)  
82604 Series (shower only)  
82613SRN (tub/shower kit with valve cap)  
L82839 Series (tub/shower)

