

AprilAire[®]

Zone Control

SPECIFICATION SHEET

Zone Control Kits

FEATURES

- Convenient – everything in one box
- Ideal for installers in residential new construction

KIT INCLUDES

- Zone Panel
- 6" Duct Probe
- 24V 40VA Universal Transformer



Model 6202K, 6203K, 6302K, 6303K

Model 6403K, 6404K

PRODUCT SPECIFICATIONS

MODEL NO.	DESCRIPTION	DIMENSIONS (H x W x L)	HUMIDITY	OPERATING TEMPERATURE	SHIPPING TEMPERATURE	VOLTAGE	MAXIMUM CURRENT
6202K	Single-Stage 2-Zone Heat/Cool Zone Board w/Sensor and 24V 40VA Transformer	9 ^{33/50} " x 8 ^{63/100} " x 1 ^{43/50} "	5%–90% RH, non-condensing	32°F–158°F	–40°F–180°F	18–30VAC 50/60 Hz	Damper output per zone (fused): 18VA at 158°F, 30VA at 90°F zone panel and thermostats (fused): 18VA at 158°F, 30VA at 90°F zone panel consumption: 4VA max Note: Use 18 or 20 AWG solid (non-stranded) wire
6203K	Single-Stage 3-Zone Heat/Cool Zone Board w/Sensor and 24V 40VA Transformer						
6302K	Single-Stage 2-Zone Heat Pump Zone Board w/Sensor and 24V 40VA Transformer						
6303K	Single-Stage 3-Zone Heat Pump Zone Board w/Sensor and 24V 40VA Transformer						
6403K	Single or Multi-Stage 3-Zone Universal Zone Board w/Sensor and 24V 40VA Transformer	14 ^{10/25} " x 8 ^{17/20} " x 1 ^{43/50} "					
6404K	Single or Multi-Stage 4-Zone Universal Zone Board w/Sensor and 24V 40VA Transformer						

