





The slim and refined lines of Sahale bring a refreshing change to today's kitchens. Bright Halogen lighting complements your cooking experience and two fan speeds make cooking more enjoyable.

SIZE	WHITE	BLACK	STAINLESS	GREASE FILTER (replacement)	NON-DUCT FILTER
30 in.	BKSA130WW	BKSA130BL	BKSA130SS	HPFA (Type Ao)	HPF1 (Type Xa)

HVI PERFORMANCE							
			Sones		CFM		
Duct Orientation	Size	Damper	Normal	High	Normal	High 0.25 in. w.g.	High 0.1 in. w.g.
Vertical - Rectangular	3¼ in. x 10 in.	Included	1.5	5.0	130	130	220
Horizontal - Rectangular	3¼ in. x 10 in.	Included	1.5	5.0	110	120	210
Round - Vertical	7 in.	Sold Separately	1.5	5.0	150	100	240

FEATURES				
Max. Blower CFM*	300			
Control type	2-speed Rocker			
Delay off	no			
Filter Clean Reminder	no			
Heat Sentry™	no			
ADA Capable	yes			
Lighting	2-level 50 W Halogen (included)			
Grease Filter	Open Mesh (Qty. 1)			
Installation Hardware	Standard			
ENERGY STAR®	no			
Recirculation	Non-ducted filter sold separately			
AC INPUT				
120 V, 60 Hz - 1.4 AMPS				
OPTIONAL ACCESSORIES				



OPTIONAL ACCESSORIES						
7-in. Round Damper	BP87Q					
Make-up Air Dampers	MD6TU, MD8TU and MD10TU					

## **MOUNTING HEIGHT**

18 in. to 24 in. from cooktop to bottom of hood


## LIMITED WARRANTY

1-year


**BKSA1 SERIES** 

SPECIFICATION SHEET

## FOR INDOOR USE ONLY







HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 and 0.25 in. static pressure at high speed based on tests conducted in an HVI-approved state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements.

<sup>\*</sup> Where noted performance rating is not HVI certified but was established in accordance with HVI Standardized test procedure.