





Delta BreezSlim

Delta BreezSlim Series

SLM50	50 CFM Single Speed (formerly VFB050B3A1)
SLM70*	70 CFM Single Speed (formerly VFB070B3A1)

Project Pack Components

SLM-A	Fan Housing Can (formerly VFB000B3A1F)			
SLM-AMTL Fan Housing Can with Metal Duct				
SLM50-B	50 CFM Motor/Grille (formerly VFB050B3A1F)			
SLM70-B	70 CFM Motor/Grille (formerly VFB070B3A1F)			

Extraordinary performance in a small package.

Weighing in at less than 5 lbs., the powerful yet compact Delta BreezSlim sets the bar for performance in the popular small fan size of 7 1/2" x 7 1/4" x 3 15/16". Operating at just 1.0 sone, this quiet fan features Delta's super reliable DC brushless motor, a LED indicator light so you know it's running, and a modern grille design. Perfect for retrofit into an existing space or for ceiling mount or wall mount installation (UL listed for both) into your next multifamily or single-family project. BreezSlim breaks the mold of the everyday bathroom exhaust fan. Available in contractor packs.



¹ Calculations based upon U.S. average retail electricity at and HVI testing labs. Actual results may vary.

² Based upon BreezSlim SLM50 vs. market AC motor fan.

³ Based upon ENERGY STAR® criteria for residential ventilating fans.





BreezSlim SLM50 (formerly VFB050B3A1) 50 CFM Single Speed Fan

Innovative DC brushless motor design for long life, low noise, and low power consumption.

- Energy savings up to 85%²
- 1 sone the quietest ever in a 7 ¹/₂" x 7 ¹/₄" bath fan
- Exceeds ENERGY STAR[®] requirement by 458% in energy efficien-CV³

Project Pack Components Available







Specifications

The Delta BreezSlim series ventilation fans deliver extraordinary power and performance in a compact design that is especially suited for challenging space requirements. Can be either ceiling or wall mounted.





Delta BreezSlim Series	SLM50 (Formerly VFB050B3A1)		SLM70* (Formerly VFB070B3A1)	
Static Pressure (Inches w.g.)	0.1	0.25	0.1	0.25
Air Flow (CFM)	50	36	70	54
Sones	1.0	1.2	2.0	1.5
Power Consumption (Watts)	6.4	6.3	13.1	11.5
Energy Efficiency (CFM/Watt)	8.9	6.5	5.8	5.0
Current (Amps)	0.18 Max		0.29 Max	
Power Rating (Volts/Hz)	120/60		120/60	
Duct Diameter	3"		3"	
Dual Speed	N	/A	N/A	
Mounting Opening	7.25″	x 7.5″	7.25″x 7.5″	
Mounting Depth	3.9	37"	3.937"	
Grille Size	9.375">	< 10.75″	9.375" x 10.75"	
Shipping Gross Weight (Lbs)	4.7	75	4.75	
cUL Tub/Shower Enclosure	Ye	25	Yes	
Washington State VIAQ Code	Ye	25	Yes	
California Title 24 Compliant	Ye	25	Yes	
Mfg in ISO 9001 Certified Factory	Ye	25	Yes	
ENERGY STAR® Qualified	Ye	25	Yes	
ENERGY STAR Most Efficient 2013	Ye	25	No	
Warranty (Years)	3	}	3	





Design and specifications subject to change without notice.