FireLock® 300 psi Solenoid

The FireLock solenoid is designed for use with Victaulic FireLock Preaction and Deluge devices that use electric actuation. Approved for NEMA 4 classification, the Series is rated to 300 psi/2065 kPa and is UL/ULC Listed and FM Approved for indoor or outdoor use. The solid brass construction provides protection against falling dirt, inclement weather, windblown dust, splashing and hose-directed water. The solenoid uses a 1/2"/21.3 mm NPT connection and is wired for 24 VDC service.

MATERIAL SPECIFICATIONS

DIMENSIONS

Body: Forged Brass

Spring: 300 Series Stainless Steel

- Seal: Fluoroelastomer
- Diaphram: Fluoroelastomer
- Wiring: 24 VDC

Voltage: 24VDC

Power Rating: 8.7 Watts

Resistance: 660hms

Current: .364 Amps

JOB/OWNER	CONTRACTOR	ENGINEER	
System No	Submitted By	Spec Sect	_ Para
Location	Date	Approved	
		Date	

www.victaulic.com

VICTAULIC IS A REGISTERED TRADEMARK OF VICTAULIC COMPANY. © 2020 VICTAULIC COMPANY. ALL RIGHTS RESERVED. PRINTED IN THE USA. **REV_D**

		D Flow	E-		
Size	Dimensions – Inches/mm			Approx. Weight Each	
Nominal Size Inches mm	A	в	С	D	Lbs./kg
1/2 21.3	3.75 95	2.75 70	1.50 38	2.96 75	1.2 0.5



– Safety Cap Coil

- Valve

- F -->

SEE VICTAULIC PUBLICATION 10.01 FOR DETAILS



30.63



FireLock® 300 psi Solenoid

	•				
INSTALLATION	Reference should always be made to the Installation, Maintenance, and Testing manual shipped with the product. Installation, Maintenance, and Testing manuals are included with each shipment of Victaulic products and are available in PDF format on our website at www.victaulic.com.				
。 WARRANTY	Refer to the Warranty section of the current Price List or contact Victaulic for details.				
。 NOTE	This product shall be manufactured by Victaulic or to Victaulic specifications. All products to be installed in accordance with current Victaulic installation/assembly instructions. Victaulic reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligations.				

