

JOB NAME: _____

DATE: _____

TYPE: _____



Accessories:



RDL6-BF-27K / RDL6-BF-30K RDL6-BF-41K / RDL6-BF-50K

LED Trims 5" and 6"

Isolated driver for improved thermal management.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120V 50/60Hz
- Wattage: 13w
- Other wattages available: 10W
- Power factor: 90% +
- Replacement: 120w

LIGHTING SPECIFICATIONS:

- Base: E26/ GU10/ GU24
- CRI: ≥90ra
- Color temperature: 2700K and 3000K (Warm white), 4100K(Natural white), 5000K (Daylight)
- Beam angle: 90°

SIZE:

- Product size: 190*80mm
- Hole size: 150mm
- Gross weight per pcs: 330kg

WARRANTY:

- Five-year warranty

MODEL NO	WATTAGE	LUMENS	COLOR TEMP
RDL6-BF-27K	13W	1080-1260lm	WW 2700K
RDL6-BF-30K	13W	1080-1260lm	WW 3000K
RDL6-BF-41K	13W	1080-1260lm	NW 4100K
RDL6-BF-50K	13W	1080-1260lm	DL 5000K

HOUSING SPECIFICATIONS:

- Housing: Spun aluminum with white powder coat finish
- Trim ring: Integrated spun aluminum white powder coat finish
- Gasket: Close cell Neoprene foam gasket
- Lens: 0.125" white translucent acrylic
- Wet locations: Suitable for damp locations
- Maximum ambient 4°C (104°F)
- Adjustable bracket can fit 5" and 6" housings

CERTIFICATIONS:

- UL listed
- ETL
- Energy Star-rated (2700K, 3000K, and 4100K)
- Pending Energy Star-rated (5000K)

