


- Available in LED & Incandescent
- White Powdercoated Aluminum
- Wall or Ceiling Mount
- UL Listed for Wet Locations
- Standard Pack QTY: 6

### SENTINEL - 10.5"



RoHS  
compliant



#### EXAMPLE # FS323-LE800W-WFO

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
<b>FS323</b>	<p><b>EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*</b>  <b>AMBIENT OP TEMP -40°C (-40°F) TO +50°C (122°F)</b>  <b>5 YEAR WARRANTY, DIMMABLE, ENERGY STAR</b></p> <p><b>LE800</b> - 13W Power Input      <b>W</b>-900lm 3000K                      CRI 80 (TYP)                      <b>C</b>-1000lm 4000K                      &gt;65 Lumens Per Watt**</p> <p><b>LE1200</b> - 14W Power Input      <b>W</b>-1350lm 3000K                      CRI 80 (TYP)                      <b>C</b>-1400lm 4000K                      &gt;80 Lumens Per Watt**</p> <p><b>LE1800</b> - 23W Power Input      <b>W</b>-1850lm 3000K                      CRI 80 (TYP)                      <b>C</b>-1900lm 4000K                      &gt;80 Lumens Per Watt**</p>	<b>W</b> -White	<b>ACRYLIC</b> <b>F</b> -Glare Reduced Frost Prismatic	<b>O</b> -Occupancy Sensor
	<p><b>INCANDESCENT, MEDIUM BASE, 120V</b>  <b>ENERGY STAR WITH LAMP OPTION</b>  <b>I240-2 X 40W Max</b></p>	<b>W</b> -White	<b>ACRYLIC</b> <b>F</b> -Glare Reduced Frost Prismatic	<b>LSW</b> -9W, 2700K, LED Lamp <b>LSC</b> -9W, 4000K, LED Lamp

\*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST    \*\*ESTIMATED FROM LED SOURCE    \*\*\*ONLY AVAILABLE ON 14" MODEL



Scan the QR code to the left to access the Energy Star qualified product list.