

Toll-Free: 1-800-462-4983



ELECTRO TAPE

Duct Tape



Electro Tape duct tapes utilize triple-layer construction consisting of a polyethylene (PE) plastic backing for waterproofing, a cloth middle layer that provides strength and affords a straight tear, and a quality rubber-based adhesive for durable holding power.

Economy and Utility Grade duct tapes offer good adhesion in short-term, low-demand applications on relatively clean surfaces with light weather exposure.

General Purpose and Contractor Grade tapes have a higher cloth thread count for greater strength, a thicker PE backing for increased durability and more adhesive for better holding power – particularly in typical construction environments.

Professional and Premium Grade tapes are constructed for long-term, high demand applications. They often contain additives or special formulations, which provide resistance to sunlight and harsh conditions.

Mfg Part#	Size	Color	Adhesion	Tensile Strength	Case Qty
200 Series – 7 mil Economy Grade; great for general purpose bundling, film patching, and light duty applications					
20002	2" x 60 yd	Silver	45 oz/in	21 lb/in	24
206 Series – 8 mil Utility Grade; enhanced adhesion allows for great versatility					
20602	2" x 60 yd	Silver	50 oz/in	22 lb/in	24
204 Series – 9 mil General Purpose; excellent blend of value and performance for general purpose applications					
2042022	2" x 60 yd	Red	55 oz/in	23 lb/in	24
20409	2" x 60 yd	Black	55 oz/in	23 lb/in	24
204302	3" x 60 yd	Silver	55 oz/in	23 lb/in	16
204402	4" x 60 yd	Silver	55 oz/in	23 lb/in	12
203 Series – 10 mil Contractor Grade; good for hanging poly and some applications where clean removal is a benefit					
20303	3" x 60 yd	Silver	45 oz/in	24 lb/in	16
20304	4" x 60 yd	Silver	45 oz/in	24 lb/in	12

ELECTRO TAPE

Vinyl Electrical Tape: 65 Series
GENERAL PURPOSE

Effective for use in industrial applications for permanent bundling or wrapping where conformability and aging resistance are critical.

- 7-mil Economical all-purpose black electrical tape
- Provides moisture-tight electrical and mechanical protection
- Weather resistant; resists UV rays, acids, alkalis, abrasion, moisture, and corrosion
- Temperature range: 0°C to 80°C
- Wound on 1.5" ID core



Mfg Part#	Size	Case Qty
12060	3/4" x 60 ft	200

ELECTRO TAPE

Color Coding Vinyl Tape: 60 Series
GENERAL PURPOSE



Effective for use in non-electrical industrial applications for permanent bundling or wrapping where conformability and aging resistance are critical.

- 7-mil general purpose color coding vinyl tape
- Suitable as a phasing tape for electrical conduit, circuit wires, motor leads, splices and terminations.
- Very conformable – provides moisture-tight electrical and mechanical protection.
- Resists UV rays, acids, alkalis, abrasion, moisture, and corrosion.
- Available in nine colors.
- Temperature range: 0°C to 80°C
- Wound on 1.5" ID core.

Mfg Part#	Size	Color	Case Qty
15060	3/4" x 66 ft	Purple	100
15061	3/4" x 66 ft	Yellow	100
15062	3/4" x 66 ft	Red	100
15063	3/4" x 66 ft	White	100
15064	3/4" x 66 ft	Orange	100
15065	3/4" x 66 ft	Blue	100
15066	3/4" x 66 ft	Brown	100
15067	3/4" x 66 ft	Grey	100
15068	3/4" x 66 ft	Green	100



Local: 972-247-8871

ELECTRO TAPE

Masking Tape: 250 Series

GENERAL PURPOSE

Used for a range of packaging, bundling, holding, splicing, masking and labeling applications.

- General purpose tape offering both economy and versatility
- Crepe paper backings to provide stretch and conformability
- Quality adhesive for great adhesion to delicate as well as solid surfaces
- Rated service temperature 32°F to 160°F (Not suitable for solvent based paints or oven bake cycles)
- Tape Thickness: 5.0 mil
- Adhesion: 28 oz/in
- Tensile Strength: 19 lb/in
- Elongation: 6%



Mfg Part#	Size	Case Qty
25002	3/4" x 60 yd	48
25004	1" x 60 yd	36
25008	2" x 60 yd	24
25009	3" x 60 yd	12

ELECTRO TAPE

Masking Tape: 108 Series

DAY BLUE – CLEAN REMOVAL PAINTERS GRADE

Excellent tape for even the most demanding paint applications. Hold up poly on walls; hold down floor covers, etc.

- UV resistant product with a specially formulated adhesive system permits clean removal from a wide variety of surfaces up to 14 days
- Highly versatile product suitable for use on glass, most wallpaper, metal, painted or unpainted wood, and stained or painted wallboard
- Not recommended for lacquer applications
- Tape Thickness: 5.5 mil
- Adhesion: 22 oz/in
- Tensile Strength: 22 lb/in
- Elongation: 6%



Mfg Part#	Size	Case Qty
25544	1" x 60 yd	36
25546	1.5" x 60 yd	32
25548	2" x 60 yd	24

ELECTRO TAPE

Carpet Protection Film: 22 Series



A tough 3 mil PE clear film that is specifically designed for carpet protection from various types of soiling. Custom formulated adhesive system offers excellent adhesion to most types of carpeting and can be kept in place for up to 45 days. All rolls are reverse wound for easy one person application. Just begin, apply where desired and roll out like a carpet. This product is designed for use on carpet only.

Mfg Part#	Size	Case Qty
59236200	36" x 200 ft	36

ELECTRO TAPE

Sticky-Mat

Dirt grabbing mat lifts dirt and debris from shoes and wheels, but will not leave a residue. Each mat has 30 sheets of exposed low-tack adhesive that collects and prevents foot traffic contamination. Peel top sheet away to reveal the next clean layer. Heavy duty non-skid base is available for use with 24" pads. Base prevents slipping and allows for easy relocation of entire system.



Mfg Part#	Size	Color	Pack	Case Qty
TMAT24B	24" x 36"	Blue	30 sheets / pad	10 pads

Toll-Free: 1-800-462-4983



ELECTRO TAPE

STUCK-O-TAPE: 145 Series
Stucco/Trim Protection Mask

30-Day Stuck-O-Tape™ is the brand of choice for stucco professionals. It is a conformable low density polyethylene film, coated with an aggressive rubber-resin adhesive offering excellent aging characteristics – weather and UV resistant. Ideal for indoor or outdoor use as a surface protection and masking tape. Removes easily from surfaces as varied as masonry, wood, vinyl, painted metal and glass even after prolonged periods up to 30 days. Primarily used to mask window and door frames during stucco application to protect from over-spray.



- All products are hand tearable
- Tape Thickness: 7.5 mil
- Adhesion: 35 oz/in
- Tensile Strength: 12 lb/in
- Elongation: 450%

Mfg Part#	Size	Color	Case Qty
145202	2" x 60 yd	Red	24

ELECTRO TAPE

Duct Protection Film: 5993 Series
PREMIUM GRADE

Tough self-adhesive 3 mil blue PE film for great puncture resistance and a high tack adhesive for better hold. Specifically designed to be applied at the time of fabrication over the openings of ductwork systems. Film protects uninstalled HVAC duct during storage and shipping from dirt, dust, moisture, insects and other contaminants that can lead to poor air quality. Specially formulated adhesive system will adhere to the duct during transport and will not leave residue once removed. Film is strong and puncture resistant.



Mfg Part#	Size	Case Qty
599324B-200	24" x 200 ft	1

ELECTRO TAPE

Barricade Tape: 865 Series
CAUTION YELLOW

Barricade tapes are an economical way to mark, identify and protect workers and visitors from job site dangers. These products offer a long lasting marking solution for off-limit areas or crowd control.



- Designed to protect & identify both above & below ground hazardous areas
- Long lasting marking solutions for off-limit areas or crowd control
- 2mil true thickness (not nominal)

Mfg Part#	Text Displayed	Size	Case Qty
86501	CAUTION CAUTION	3" x 1000 ft	8
86511	CAUTION CUIDADO	3" x 1000 ft	8

ELECTRO TAPE

Barricade Tape: 866 Series
DANGER RED

Barricade tapes are an economical way to mark, identify and protect workers and visitors from job site dangers. These products offer a long lasting marking solution for off-limit areas or crowd control.



- Designed to protect & identify both above & below ground hazardous areas
- Long lasting marking solutions for off-limit areas or crowd control
- 2mil true thickness (not nominal)

Mfg Part#	Text Displayed	Size	Case Qty
86601	DANGER DANGER	3" x 1000 ft	8

ELECTRO TAPE

Flagging Tape: 870 and 875 Series
NON-GLOW AND GLOW

Typically used in construction environments for surveying, mapping, and roping off an area.

- Non adhesive PVC carrier ensures no residue left behind
- Glow version designed to provide greater visual impact



Mfg Part#	Color	Size	Case Qty
87001	Yellow	1-3/16" x 300 ft	144
87002	Red	1-3/16" x 300 ft	144
87003	White	1-3/16" x 300 ft	144
87004	Orange	1-3/16" x 300 ft	144
87005	Blue	1-3/16" x 300 ft	144
87008	Green	1-3/16" x 300 ft	144
87501	YellowGlo	1-3/16" x 150 ft	144
87502	RedGlo	1-3/16" x 150 ft	144
87504	OrangeGlo	1-3/16" x 150 ft	144
87506	PinkGlo	1-3/16" x 150 ft	144
87508	LimeGlo	1-3/16" x 150 ft	144

ELECTRO TAPE

Woven Barricade: 892 Series

Heavy duty woven polypropylene film ensures long life.

- High tensile strength (275 #) provides a rigid barrier resistant to high winds and rigorous impact.
- Yellow or Red woven carrier with solid black line down through web center.



Mfg Part#	Size	Color	Case Qty
892150	2" x 150 ft	Yellow/Black	48
893150	2" x 150 ft	Red/Black	48



Local: 972-247-8871

ELECTRO TAPE

Thread Seal: 550PQ Series
CONTRACTOR GRADE

Used for wrapping and sealing the threads of iron, copper, brass, plastic, glass or rubber pipes to ensure leak proof connections. Provides chemically inert, no hardening, non-contaminating permanent seal. Meets military specification MIL-T-27730A (superseded by A-A-58092).

- Made in China
- Tape Thickness: 4mil
- Standard Density: 0.28 gm/cm3 – 100% virgin PTFE
- Suitable for standard, non-challenging thread seal requirements
- Temperature range - 375°F to 500°F



Mfg Part#	Size	Case Qty
55008PQ	.5" x 520"	1000
55010PQ	.75" x 520"	700

ELECTRO TAPE

Carton Seal: 805 and 808 Series

Clear carton sealing tapes feature a non-yellowing and UV resistant acrylic based adhesive system carried on conformable polypropylene backings. Our acrylic carton sealing tapes are made to higher standards than most imported tapes to ensure consistency and reliability in performance – from first case to last. Tapes are available in both water based systems (for balance of price & performance) and solvent based systems (highest clarity, premium adhesion and longevity). Acrylic tapes can be stored and used for extended periods of time while their performance properties remain constant even in climate extremes. They offer great clarity and visual appeal and possess UV stability.

- Operating Temperature: 32°F to 150°F.



Mfg Part#	Size	Color	Adhesion	Tensile Strength	Case Qty
805 Series – 2 mil General Purpose					
80575	2" x 110 yd	Clear	22 oz/in	24 lb/in	36
80585	3" x 110 yd	Clear	22 oz/in	24 lb/in	24
808 Series – 2.6 mil Premium					
80875	2" x 110 yd	Clear	26 oz/in	27 lb/in	36

ELECTRO TAPE

Pallet Wrap: 80G Series
80 GAUGE HANDWRAP

A high performance hand wrap designed to securely unitize irregularly shaped and difficult to wrap loads. Manufactured of a quality three layer, cast, coextruded, linear low density polyethylene film with both side cling. Excellent load retention and stretch memory.

- Good puncture resistance, tensile strength, elongation and performance
- Excellent load retention and stretch memory
- Provides compressive force for tighter load holding
- Will perform consistently at higher stretch levels, resulting in excellent cost performance value



Mfg Part#	Size	Case Qty
91280	18" x 1500 ft	4

ELECTRO TAPE

Filament Strap: 199 Series
100 lb ECONOMY

Our strapping tapes are available in both tensilized polypropylene and reinforced filament constructions. Tensilized Polypropylene tapes have extra tensile strength in the machine direction and carry low tack adhesives. These features make these tapes best for light weight, temporary bundling applications such as pallet wrapping. Filament tapes use fiberglass threading which imparts superior tensile strength. As the thread count increases so does the final breaking strength. Our filament tapes are constructed using conformable polypropylene backing, fiberglass filaments, and aggressive synthetic rubber adhesive.



Mfg Part#	Size	Case Qty
300107	3/4" X 60 yd	48
300120	2" x 60 yd	24

ELECTRO TAPE

Packing List Envelopes: 950 Series

- With window – easy to view documents.
- Pressure sensitive application



Mfg Part#	Size	Case Qty
95000	4.5" x 5.5"	1000

Toll-Free: 1-800-462-4983



ELECTRO TAPE

Aluminum Foil Tape: 322 Series
UTILITY GRADE

Engineered for a wide range of applications and environments. Foil tapes are known for their features of superior conformability, moisture resistance, and durability over a wide range of environmental conditions (broad temperatures and high humidity). These features make foil tapes the best choice for vapor sealing of irregular and fibrous duct work, seaming of fabricated metals, and sealing of leaks and cracks in high demand applications. Constructions include aluminum foil, reinforced foil (FSK), and metalized films and tapes.



- 2 mil Foil
- Rubber Adhesive provides high adhesion and quick stick for strong initial bond
- UL Listed
- Seal duct work for heating, air conditioning and refrigeration systems.
- Moderate temperature range. Max Temperature: 200°F
- Tape Thickness: 5.0 mil
- Adhesion: 130 oz/in
- Tensile Strength: 15 lb/in

Mfg Part#	Size	Case Qty
51322	2" X 50 yd	24

ELECTRO TAPE

Clean Room Tape: 150C Series
PVC

- Soft white PVC film tape designed specifically for clean room applications where contaminant / dust control is critical
- Tape is provided on a 3" Plastic Core and each roll wrapped to meet Clean room requirements.
- Tape Thickness: 6.0 mil
- Adhesion: 30 oz/in
- Tensile Strength: 18 lb/in
- Elongation: 160%



Mfg Part#	Size	Case Qty
155203N	2" x 36 yd	24

ELECTRO TAPE

Vapor Barrier Poly Seam Tape: 145VT Series
w/ RUBBER ADHESIVE

Film "Poly" tapes are a versatile alternative to traditional duct tapes. They can be used in permanent as well as temporary protective applications. Two unique film constructions, low density polyethylene (LDPE) and vinyl (PVC), provide excellent flexibility, conformability and stretch. These backings are resistant to wear (masking), moisture (barrier seams), chemicals, and aging (UV exposure). The adhesive systems are specially formulated to provide superior adhesion and hold even in applications where surfaces are textured or dust and dirt adds a challenge. This blend of properties make poly tapes a premium choice for construction and outdoor environments.



- The low permeability rating for this tape prevents moisture and vapor flow making this an excellent splice tape for heavy duty films for floor underlay.
- MVTR rating: 0.20 perms
- Resists outdoor exposure, moisture, chemicals and weathering
- Red color provides high visibility to ensure seam splice has been completed
- Tape Thickness: 7.5 mil
- Adhesion: 35 oz/in
- Tensile Strength: 12 lb/in
- Elongation: 450%

Mfg Part#	Size	Case Qty
145402	4" X 60 yd	12