



PTR188700-PFS-PX
PTR188700-PFS-PXWS
PTR188700-PFT-PX
PTR188700-PFT-PXWS

Rough-In:

PTR188700-PFX-PX

PEX crimp inlet & outlet, shower only, without stops

PTR188700-PFS-PXWS

PEX crimp inlet & outlet, shower only, with stops

PTR188700-PFT-PX

PEX crimp inlet & outlet, with tub drop, without stops

PTR188700-PFT-PXWS

PEX crimp inlet & outlet, with tub drop, with stops

STANDARD SPECIFICATIONS:

- Pressure Balance Valve Body.
- Back-to-back installation capability.
- Cartridge utilizes integral check valves to prevent the cross flow of water within the valve. Valve reduces the flow of water to 0.5 GPM within 5 seconds of the complete loss of pressure in the cold water supply line. Outlet water temperature is maintained within $\pm 3^\circ\text{F}$ variation with changes in either hot or cold supply of up to 50 percent of the normal supply pressure. Temperature is controlled by handle with cold water always coming on first.
- Forged brass body.
- Field adjustable means to limit handle rotation into hot water zone.
- Temperature control to rotate a maximum of 120° from full cold to the maximum temperature.
- Single Handle.
- Temperature Only Controlled with Handle.

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or, for commercial users, for 5 years from the date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASSE 1016