

SLATER

Features

- · Solid brass construction
- Face plate with 3-spoke circular handle
- 1.8 gallons (6.7 liters) per minute maximum flow rate showerhead
- Intended for use with Newport Brass rough valve(s) as specified (Required Accessory)

Shower Trim **3-2924BP**

Also 3-570

Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- IPC
- ICC/ANSI A117.1
- ASSE 1016
- Energy Policy Act of 1992
- EPA Watersense
- California Energy Commission (CEC)
- All applicable US Federal and State material regulations





3-570

Colors / Finishes

10B: Oil Rubbed Bronze
15: Polished Nickel
15S: Satin Nickel - PVD
26: Polished Chrome

• Other: Refer to the Newport Brass catalog for additional color/finish options.

3-2924BP

Specified Model Description Colors | Finishes Model 3-2924BP **Shower Trim** Other 10B 15 15S 26 3-570 Shower System Control Valve Trim (Escutcheon/Handle) 15S Other 10B 15

Required Accessory: Trim(s), above, and Rough Valve(s), below, must be specified. Application Shower (or Tub) Valve (Choose One) Control Valve

Application	Shower (or rab) varve (choose one)		Control valve
Description	Balance Pressure (BP)	Balance Pressure (BP)	Diverter (3/4 Port)
Inlet/Outlet Size	1/2"	1/2"	1/2"
Part Number	1-594	1-684	1-617
Image			

Product Specification: Add "Color / Finish" suffix to Model number, below.

The single-control Shower Trim shall be made of solid brass construction. Shower Trim shall include showerhead with arm and flange and faceplate with 3-spoke circular handle. Showerhead shall have a maximum flow rate of 1.8 gallons (6.7 liters) per minute. Shower Trim shall be Newport Brass Model 3-2924BP /____ and single-control Shower rough valve shall be Newport Brass Model 1-____. [Optional Shower System Control Valve Trim (Escutcheon/Handle) shall be 3-570/____ and Shower System Control Valve shall be 1-617].

3-2924BP

PRODUCT DIMENSIONS (Units are in inches)

