

OPTIONS

Flush Volume

- 1.6 gpf (6.0 Lpf) (1.6)
- 3.5 gpf (13.2 Lpf) (3.5)
- 1.28 gpf (4.8 Lpf) (1.28)
- 4.5 gpf (17 Lpf) (4.5)

Water Efficiency

- Low Consumption
- Water Saver
- High Efficiency

Bypass

- Dual-Filtered Fixed Bypass Diaphragm (DFB)

Handle

- Sanigard® (SG)
- Front of Valve (H)
- Nickel-Silver (YA)

Push Button

- 3" Metal Oscillating (L3)
- Front of Valve (HL3)

Control Stop

- Less (L/STOP)

Offset

- 1 ½" (38mm) (1-1/2-OFST)
- 2" (51mm) (2-OFST)
- 1" (25mm) (1-OFST)

Outlet Tube

- F189 (F189)
- F190 (F190)
- Trap Primer (TP)
- F188 (F188)

Bumper

- Double Wall (YI)

Pipe Support

- Solid Ring (YK)
- Split Ring (YJ)

Special Features

- 2 Wall Bumpers (Y1)

Compliances & Certifications

- BAA Compliant
- ADA Compliant
- cUPC Certified



DESCRIPTION

Sloan® Exposed Manual Specialty Water Closet Bedpan Washer Flushometer

FEATURES

- Exposed water closet, diaphragm type, chrome-plated Flushometer for floor-mounted or wall-hung top spud bowls and for installation where clearance is required around grab bars
- Meets ADA height requirements
- Automatically operates by means of a self-adaptive infrared sensor
- Presents a leaner, more aesthetic installation, reducing possible bacteria growth on hidden and hard-to-reach surfaces found on other bedpan washer units
- Eliminates the need for unsanitary hose sprays, as well as the additional housekeeping that hoses require and the potential for patient slippage
- Incorporates a patented one-piece construction body design, maintaining the spray arm in an upright position
- Valve body, stop body, diverter body and diverter pivot made from brass casting using semi-red brass for durability and long life
- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

UPC Certified
BREEAM Water Credit
Green Globes Water Credit
LEED V4 Water Efficiency Credit
Satisfies LEED Credits
WaterSense Listed
cUPC Green Certified

DOWNLOADS

- [Sloan Concealed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Slimline Bedpan Washer Repair and Maintenance Guide](#)
- [Additional Downloads](#)

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.