



*This Part requires two clamps, part number 164-300.
See additional drawing for information on these clamps.

NOTES:
-SOME HIDDEN LINES NOT SHOWN
-BREAK ALL SHARP CORNERS
-REPORT ALL CHANGES TO ENGINEERING

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERNCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FERNCO, INC. IS PROHIBITED.

Part Weight	3.635 lbs.
Min/Max Temp.	-30/140 Degrees F
Pressure Tested	4.3 PSI
Material	Flexible PVC
Installation Torque	60" Lbs.
Conforms to ASTM	D5926, C1173
Box Quantity	10
Clamps used	300 Series

TOLERANCES:
.X= Fractional ±
.XX= ±.02
.XXX= ±.030
ANG.= ±0.5°
UNLESS OTHERWISE SPECIFIED

DESCRIPTION:
Coupling 8" Ductile Iron, A/C Fibre
x 8" Ductile Iron, A/C Fibre

1055-88

UNITS:	SIZE:	DESIGNER:	SCALE:
INCHES	A	D. Brady	not to scale
3RD ANGLE PROJECTION DO NOT SCALE DRAWING		CHECKER:	DATE: 2/1/2007
			SHEET 1 OF 1