

Proximity® ANSI • CE • CSA •



FOAM
PADDING



CO-INJECTED
TEMPLES

Removable flame resistant foam padding // Lightweight
spectacle – 26.3gm // Slim co-injected temples //
Custom imprinting available

Black Frame | 6 Variations

- SB9310ST • • • Clear **H2X** AF
- SB9310STM • • • Clear **H2MAX** AF
- SB9323ST • • • Dark Gray **H2X** AF
- SB9323STM • • • Dark Gray **H2MAX** AF
- SB9330ST • • • Amber **H2X** AF
- SB9380ST • • • I/O Mirror AF

Black and Lime Frame | 2 Variations

- SBL9310STM • • • Clear **H2MAX** AF
- SBL9323STM • • • Dark Gray **H2MAX** AF



SB93

Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB9310ST	P Z87 + U6	P Z87 + / P c SEI Z94.3	Weight: 26.3 gm	Lens: polycarbonate
SB9310STM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3	PD: 64 mm	Temples: polycarbonate & thermoplastic elastomers (TPE)
SB9323ST	P Z87 + S	P Z87 + / P c SEI Z94.3	Bridge: 16.5 mm	Hinge: polycarbonate
SB9323STM	P Z87 + S X	P Z87 + / P c SEI Z94.3	Lens base: 9.5 curve	Screw: stainless steel
SB9330ST	P Z87 + U6	P Z87 + / P c SEI Z94.3	Lens size diagonal: 75.8 mm	Foam gasket: nylon & ethylene-vinyl acetate (EVA) foam
SB9380ST	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3	Lens size vertical: 50.4 mm	
SBL9310STM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3	Lens thickness: 1.6 mm	
SBL9323STM	P Z87 + S X	P Z87 + / P c SEI Z94.3	Overall length (lens - tip): 161 mm	
Lens Marking Symbols			Overall width (hinge - hinge): 135 mm	
P: Manufacturer's mark			Closest point between temple tips: 77 mm	
Z87: ANSI standard for eye and face protection devices			Closest point between lens: 14.5 mm	
+: High impact				
S: Special Purpose				
X: Tested Anti-fog				
UV Filter Transmittance				
U6: .01% max effective far UV • .1% max near UV				
Visible Light Filters				
L1.7: 55% Max. Visible Light				
Temple Marking Symbols				
P: Manufacturer's mark				
Z87: ANSI standard for eye and face protection devices				
+: High impact				
c SEI Z94.3: CAN/CSA standard for eye and face protection devices				