

NOX-5634

5"/6" Onyx Adjustable Retrofit

Source: 12.5W LED

750lm

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

Onyx 5"/6" Round Series is suitable for use with most 5" and 6" recessed housings. Die-cast aluminum construction provides clean sharp edges. Deep regressed optics and round aperture delivers even and glare-free illumination

FEATURES

- 750lm / 12.5W
- 2700K, 3000K or 4000K @ 90+ CRI
- Integral dimmable driver
- Includes medium base socket adaptor for easy retrofitting in 5" or 6" recessed housings
- 5-year limited warranty
- Energy Star certified
- cULus classified for wet locations

SPECIFICATION

Trim: One piece, die-cast aluminum construction dissipates heat and extends life. Unitized Thermal Management, UTM, provides exceptional cool operation.

Housings: Compatible with most 5" and 6" IC and non-IC housings by Nora and others.

Mounting: Two steel, spring mounting springs allow for easy and secure mounting in most 5" and 6" housings.

Optics: Nora specified and designed precision-molded lens for optimal lumen output and even distribution. The white polymer lens diffuser evenly distributes the light.

Retrofit: Onyx retrofit series includes medium base screw-socket adapter (NRA-21ISM) for retrofitting into existing medium base downlight housings. GU24 socket adapter is available for use with GU24 housings, must specify NRA-212SM.

ELECTRICAL

Input Voltage: 120V

Lumens / Wattage: 750lm / 12.5W

Color Temperature: 2700K, 3000K or 4000K

CRI: 90+CRI

Dimming: Down to 5% with ELV or 10% with Triac

[Click Here](#) or check complete dimmer list at

www.NoraLighting.com in the "Compatibility" page under "Resources" tab

COMPATIBLE HOUSINGS

Onyx reflectors are compatible with most 5" & 6" IC and Non-IC housings by Nora and others.

Fire Box

- NFBIC-5INCATA 5" ICAT Fire Box
- NFBIC-5LMRATA* 5" ICAT Dedicated LED Fire Box
- NFBIC-6INCATA 6" ICAT Fire Box
- NFBIC-6LMRATA* 6" ICAT Dedicated LED Fire Box

New Construction

- NHIC-5LMRAT* 5" ICAT Dedicated LED
- NHIC-5LMRAT/277*¹ 5" ICAT Dedicated LED, 277V
- NHIC-527LMRAT* 5" ICAT Shallow Dedicated LED
- NHIC-501QAT 5" ICAT Line Voltage
- NHIC-527QAT 5" ICAT Shallow Line Voltage
- NH-501Q 5" Line Voltage
- NHIC-5G24ATFL 5" ICAT GU24
- NHIC-6LMRAT* 6" ICAT Dedicated LED
- NHIC-6LMRAT/277*¹ 6" ICAT Dedicated LED, 277V
- NHIC-27LMRAT* 6" ICAT Shallow Dedicated LED
- NHIC-17QAT 6" ICAT Line Voltage
- NHIC-17QNBAT 6" ICAT Line Volt (No Bracket)
- NHIC-27QAT 6" ICAT Shallow Line Voltage
- NH-26Q 6" Line Voltage
- NH-26QNB 6" Line Voltage (No Bracket)
- NHIC-6G24ATFL 6" ICAT GU24

Remodel

- NHRIC-5LMRAT* 5" ICAT Dedicated LED
- NHRIC-527LMRAT* 5" ICAT Shallow Dedicated LED
- NHRIC-504QAT 5" ICAT Line Voltage
- NHRIC-527QAT 5" ICAT Shallow Line Voltage
- NHR-504Q 5" Line Voltage
- NHRIC-5G24ATFL 5" ICAT GU24
- NHRIC-6LMRAT* 6" ICAT Dedicated LED
- NHRIC-27LMRAT* 6" ICAT Shallow Dedicated LED
- NHRIC-17QAT 6" ICAT Line Voltage
- NHRIC-17QNBAT 6" ICAT Line Volt (No Bracket)
- NHRIC-27QAT 6" ICAT Shallow Line Voltage
- NHR-26Q 6" Line Voltage
- NHRIC-6G24ATFL 6" ICAT GU24

* Nora LED Dedicated housings are cULus listed for use only with Nora LED Retrofits.

¹ Housings include a step down transformer

LABELS AND LISTINGS

- cULus classified for Damp Locations
- ENERGY STAR certified
- [5-Year Limited Warranty](#)
- Meets ASTM-E283 Air-Tight requirements
- Certified to the high efficacy requirements of California Title 24 JA8-2019





PRODUCT IMAGES AND DIMENSIONS



NOX-5634WW
Adjustable, White



NOX-5634WW / NOX-560R-W
White Oversize Ring



5"/6" Onyx Adjustable Retrofit

Lumens / Wattage / Color Temperature

NOX-563427WW = 750lm / 12.5W / 2700K

NOX-563430WW = 750lm / 12.5W / 3000K

NOX-563440WW = 750lm / 12.5W / 4000K

Optional Accessories

Description

NOX-560R-W = 5"/6" Round Oversize Ring, White

NOX-56BLADE = 5"/6" Blade for housings without spring brackets

NRA-21ISM = Medium base screw-in socket (included w/luminaire)

NRA-212SM = Socket adapter for use with GU24 housing

Example: **NOX-563440WW** = 5"/6" Onyx Round Adjustable LED Retrofit, 4000K, White finish, 750lm / 12.5W