



Corrugated Stainless Steel Flexible Water Heater/Softener Connectors Specification Sheet

SPECIFICATION:

Furnish and install Corrugated Stainless Steel Water Heater &/or Softener Connectors

DESIGN FEATURES: Mega-flow SUPER Water-flex™

- 304 Series Stainless Steel
- True .725" ID
- Flows approx. 135% more than braided type
- Maintains optimum flow – no restriction
- Kink and Crimp Free
- Chrome plated brass nut
- Extremely Flexible
- Will not corrode or rust
- No Dielectric union required!
- High Temp EPDM Washer
- Chlorine and Chloramine Resistant
- Resists work hardening
- Working pressure 200 psi
- Burst pressure approx 1850 psi
- 100% Leak Tested
- Lifetime Warrantee
- Temperature rating -40 to 220 degrees F
- Bright annealed

COMPLIANCES/LISTINGS:

- * ICC-ES PMG File #1077
- * ICC Listed, Tested & Certified
- * Complies with UPC, IPC, IMC, IRC, CSA
- * Low Lead Compliant ICC File # 1078
- * ASME A112.18.6 Compliant
- * NSF-61 (ICC-ES PMG Certified to ANSI/NSF section 9)

<u>Model #</u>	<u>Description</u>	<u>Length</u>
H3406	3/4" ULTRA FLEX	6,12,15,18,24"

3/4" FIP x 3/4" FIP – Ultra Flex – excellent for rental tanks where change-outs occur frequently and additional flexibility is desired.
Full Port No reduction in flow



<u>Product Submittal</u>	
<u>Job Name:</u>	_____
<u>Date:</u>	_____
<u>Model#</u>	<u>Quantity:</u>
_____	_____
<u>Architect/Contractor:</u>	

