



- NOTES:**
- FEATURES:**
- SMOOTH SURFACE APPEARANCE ON WALLS.
 - NON-SKID TEXTURED BOTTOM SURFACE.
 - INTEGRAL HYDROBERM FEATURE FORMS AN EFFECTIVE SPLASH GUARD ALONG THE TOP EDGE OF THE TUB/SHOWER ENCLOSURE.
 - GREEN FRIENDLY TUBS AND SHOWERS: UTILIZING ADVANCED CHEMISTRY THAT YIELDS, HIGHER QUALITY, GREATER STRENGTH AND LOWER EMISSIONS.
- TECHNICAL SPECS:**
- GEL COAT THICKNESS .020" ± .005".
 - 1ST LAMINATE .125" NOMINAL THICKNESS
 - BOTTOM IS REINFORCED WITH PERFORMANCE CORE TO MEET 300# LOAD TEST.
 - 2ND LAMINATE COMPLETELY COVERS ALL AREAS.
 - SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

J.P.C. MODEL ID



UNIT PART NUMBERS		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE AS FOLLOWS		FIBER CARE BATHS, INC.		9832 Yucca Rd. Adelanto, CA 92301 Phone: 760-246-0019 Fax: 760-246-5189	
RIGHT HAND UNIT WS48-34	DECIMAL: .XX =+.010 .XXX =+.005	FRACTIONAL: $\pm \frac{3}{8}$ "	TITLE: SHOWER STALL, 3 WALL				
LEFT HAND UNIT WS48-34	CAPACITY / OPERATING LEVEL:	GAL	DRAWN: TBN				
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FIBER CARE BATHS, INC. ANY REPRODUCTION OR UNAUTHORIZED USE IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FIBER CARE BATHS, INC. IS STRICTLY PROHIBITED. PRODUCT CONFIGURATION, DIMENSIONS, STANDARD ACCESSORIES, MATERIALS COMPOSITION AND CONSTRUCTION ARE SUBJECT TO CHANGE WITHOUT NOTICE.	CAPACITY / OVERFLOW LEVEL:	GAL	SIZE: A		MODEL #: WS48-34		REV: 1
	APPROX. UNIT WEIGHT:	LBS	DATE: 5/3/2018		SCALE: NTS		STATUS: IAPMO LISTED
	APPROX. SHIPPING WEIGHT:	LBS					