FIGURE 7251

BEAM CLAMPS



RETROFIT BEAM CLAMP RETAINING STRAP

The FNW 7251 retrofit beam clamp retaining strap is used to secure beam clamps and threaded rod to an I-beam to eliminate potential movement caused by vibration.

FEATURES

- UL Approved
- For use with 3/8" and 1/2" rod sizes
- The retaining strap shall wrap around the beam flange no less than 1 in. (25mm)
- Made in the USA

PRODUCT SPECIFICATIONS

Material Specifications and Finishes

Carbon Steel – ASTM A1011-00 SS GR 33 or ASTM A1011-00CS Type B $\,$

Z: ASTM A653 G-90 Pre-galvanized zinc (standard finish) is produced by continuously rolling steel coils or sheets through molten zinc at the mills. The coils or sheets are slit to size and fabricated by forming, shearing or punching to produce the finished product. During fabrication cut edges are not generally zinc coated; however, the zinc near the uncoated metal becomes a sacrificial anode to protect the bare areas.



Catalog Number	Cours	Beam Size		Length		Weight	
	Gauge	in.	mm	in.	mm	lbs	kg
FNW7251Z0600		6"	152	8"	203	0.158	0.072
FNW7251Z0800		8"	203	10"	254	0.204	0.093
FNW7251Z1000	16 ga.	10"	254	12"	305	0.249	0.113
FNW7251Z1200		12"	305	14"	356	0.295	0.134
FNW7251Z1400		14"	356	16"	406	0.340	0.154

