
PF2830GCP, PF2830GBN, PF2830GORB
PF2820GCP,PF2820GBN, PF2820GORB

SINGLE HANDLE TUB & SHOWER
BAÑERA Y DUCHA DE UNA LLAVE
ROBINET À UNE POIGNÉE POUR BAIGNOIRE ET DOUCHE

Installation Instructions
Instrucciones de instalación
Instructions d'installation



ENGLISH

CAUTION-TIPS FOR REMOVAL OF OLD FAUCET:

Always turn off water supply before removing existing faucet or replacing any part of the faucet. Open the faucet handle to relieve water pressure and ensure that water is completely shut off.

CARE INSTRUCTIONS:

To preserve the finish of your faucet, apply non-abrasive wax. Any cleaners should be rinsed off immediately. Do not use abrasive cleaners on the faucet.

ESPAÑOL

PRECAUCIÓN-CONSEJOS PARA CAMBIAR LA LLAVE MEZCLADORA:

Siempre corte el suministro de agua antes de retirar el grifo actual o remplazar cualquier pieza del mismo. Abra la llave del grifo para liberar la presión de agua y asegurar que ya no corre agua.

INSTRUCCIONES DE CUIDADO:

Para conservar el acabado que cubre las partes metálicas de su llave mezcladora, aplique cera que no sea abrasive, como una cera para autos. Si usa algún tipo de limpiador, deberá enjuagarlo inmediatamente. Los abrasivos suaves son aceptables en acabados platinum y LifeShine.

FRANÇAIS


ATTENTION-SUGGESTIONS POUR ENLEVER L'ANCIEN ROBIENT:

Toujours couper l'alimentation en eau avant d'enlever ou de démonter le robinet. Ouvrir le robinet pour libérer la pression d'eau et pour s'assurer que l'alimentation en eau a bien été coupée.

DIRECTIVES D'ENTRETINE:

Pour préserver le fini des pièces métalliques du robinet, appliquer une cire non abrasive comme une cire à votiure. Rincer immédiatement le robinet aprés l'avoir nettoyé avec un agent nettoyant. Les finis platinum et LifeShine peuvent être nettoyés à l'aide de produits abrasifs doux.

You may need/Usted puede necesitar/ Aticles dont vous pouvez avoir besion




Goggles Anteojos Protectores Lunettes de sécurité	Wrench Llave Clé ajustable	Standard Pliers Alicates Estándar Pinces standard	Needlenose Pliers Pinzas de Punta Larga Pinces à bec effilé	Phillips Head Screwdrivers Destornillador Phillips Tournevis cruciforme	Sealant Tape Cinta Selladora Ruban d'étanchéité	2.5mm/4.0mm Hex Allen Wrench 2.5mm/4.0mm Hex Llave Allen 2.5mm/4.0mm Cié hexagonale

PROFLO.COM

Distributed Exclusively by Ferguson and Wolseley Canada
© 2018 Ferguson Enterprises, Inc. 0102 252402

(FIG.1)




1. Insert sleeve (1) to valve body. Position escutcheon (2) on valve body with drain hole (3) at the bottom and then insert screws (4) to attach to valve body. Screw sleeve cap (5) onto thread section of valve body.

1. Coloca la funda (1) en el cuerpo de la válvula. Coloca la placa decorativa (2) en el cuerpo de la válvula con el orificio de drenaje (3) en la base y luego coloca los tornillos (4) para instalar el cuerpo de la válvula. Atornilla el remate de la funda (5) en la sección roscada del cuerpo de la válvula.

1. Insérez le manchon (1) sur le corps du robinet. Placez la rosace (2) sur le corps du robinet avec le trou d'évacuation (3) en bas, puis insérez les vis (4) pour la fixer au corps du robinet. Vissez le capuchon de manchon (5) sur la section filetée du corps du robinet.

(FIG.2)




2. Place handle (1) onto the valve and tighten set screw (2) with Allen wrench (Hex: 2.5mm).

2. Coloca la manija (1) en la válvula y aprieta el tornillo de fijación (2), usando la llave Allen proporcionada. (Hexagonal: 2,5 mm).

2. Placez la manette (1) sur le robinet, et serrez la vis de pression (2) à l'aide d'une clé hexagonale (2,5 mm).

(FIG.3)



3. FOR SHOWER ARM INSTALLATION. Insert the long end of the shower arm (2) through the flange (1) then wrap plumber's tape to both sides of shower arm. Screw long end of the shower arm into pipe elbow inside the wall.


3. INSTALACIÓN DEL BRAZO DE LA DUCHA. Inserta el extremo largo del brazo de la ducha (2) a través de la brida (1) y coloca cinta de plomero alrededor de ambos lados del brazo de la ducha. Atornilla el extremo largo del brazo de la ducha al codo de la tubería que está dentro de la pared.

3. INSTALLATION DU BRAS DE DOUCHE. Insérez la partie longue du bras de douche (2) dans la bride (1) et enveloppez les deux côtés du bras de douche avec du ruban d'étanchéité. Fixez l'extrémité allongée du bras de douche au coude de tuyau dans le mur.

PROFLO.COM

Distributed Exclusively by Ferguson and Wolseley Canada
© 2018 Ferguson Enterprises, Inc. 0102 252402

(FIG.4)




4. FOR TUB SPOUT INSTALLATION
Install tub spout. Press tub spout onto pipe until spout is properly positoned and flush to the finished wall. Tighten screw (1) located at the bottom of spout with Allen wrench (Hex: 4.0mm).

4. INSTALACIÓN DEL CAÑO DE LA TINA
Instala el caño de la tina. Presiona el caño de la tina en la tubería hasta que el caño esté correctamente ubicado y a ras con la pared terminada. Aprieta el tornillo (1) ubicado en la parte inferior del caño con la llave Allen (Hexagonal: 4,0 mm).

4. INSTALLATION DU BEC DE LA BAIGNOIRE
Installez le bec de la baignoire. Appuyez le bec de baignoire sur la conduite jusqu'à ce qu'il soit correctement positionné et de niveau avec le mur fini. Serrez la vis (1) située en bas du bec avec une clé hexagonale (4,0 mm).

(FIG.5)



5. FLUSHING
For Tub and Shower Combinations:
Turn on Hot and Cold water supply lines allowing water to flow from tub spout outlet (2) until all foreign matter has cleared the line.
For Shower Only Combinations:
Turn on Hot and Cold water supply lines allowing water to flow from shower outlet (1) until all foreign matter has cleared the line.
Pressure must be approximately equal on both Hot and Cold sides for valve to function properly.


5. PURGADO
Para combinaciones de tina y ducha:
Abre las líneas de suministro de agua fría caliente y deja que el agua salga por el caño de la tina (2) hasta que todos los desechos sean expulsados.
Para combinaciones de ducha solamente:
Abre las líneas de suministro de agua fría caliente y deja que el agua salga por el caño de la ducha (1) hasta que expulse todos los desechos.Para que la válvula funcione correctamente la presión del agua debe ser la misma en la salida del agua caliente y en la salida del agua fría.

5.ÉVACUATION
Pour l'installation du bec de baignoire et du bras de douche :
Ouvrez l'alimentation en eau chaude et en eau froide pour faire circuler de l'eau dans la sortie du bec de la baignoire (2) jusqu'à ce que tout corps étranger soit éliminé de la canalisation.
Pour l'installation du bras de douche seulement :
Ouvrez l'alimentation en eau chaude et en eau froide pour faire circuler de l'eau dans la sortie du bec de la douche (1) jusqu'à ce que tout corps étranger soit éliminé de la canalisation. Pour que le robinet fonctionne correctement, la pression doit être environ la même des deux côtés.


PROFLO.COM

Distributed Exclusively by Ferguson and Wolseley Canada
© 2018 Ferguson Enterprises, Inc. 0102 252402

(FIG.6)



6. Attach shower head to shower arm. 6. Fija el cabezal de ducha al brazo de la ducha. 6. Fixez la pomme de la douche au bras de douche.



PROFLO.COM

Distributed Exclusively by Ferguson and Wolseley Canada
© 2018 Ferguson Enterprises, Inc. 0102 252402

Standard Warranty

WHAT IS COVERED?

Ferguson Enterprises, Inc. “Ferguson” or the “Company” warrants its products to be free from defects in material and workmanship under normal use and service FOR A PERIOD OF ONE (1) YEAR FROM THE DATE OF INSTALLATION.

WHAT IS NOT COVERED?

The warranty set forth in paragraph 1 does not cover installation or any other labor charges and does not apply to products which have been damaged as a result of any accident, abuse, improper installation or maintenance, or modification of original plumbing product. The warranty of such products is limited to the warranty extended to Ferguson by the product manufacturer. Finally, FERGUSON SHALL NOT BE RESPONSIBLE OR LIABLE FOR ANY FAILURE OR DAMAGE TO THIS PRODUCT OR ANY COMPONENT THEREOF CAUSED BY THE USE OF ABRASIVE CLEANERS.

HOW TO OBTAIN WARRANTY SERVICE

US Customers:
The purchaser should contact their local Ferguson location, installing contractor or builder from whom the product was purchased. To find your nearest Ferguson location please visit www.ferguson.com and enter in your address into the Find a Location field.

Canadian Customers:
The purchaser should contact their local Wolseley Canada location, installing contractor or builder from whom the product was purchased. To find your nearest Wolseley Canada location please visit www.wolseleyinc.ca, then click on Find a Location and enter in your address into the location field.

LIMITATIONS OF IMPLIED WARRANTY AND DISCLAIMER OF CONSEQUENTIAL OR INCIDENTAL DAMAGES

FERGUSON DISCLAIMS ANY LIABILITY FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES AND DISCLAIMS ALL EXPRESS OR IMPLIED WARRANTIES, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AS SET FORTH ABOVE. IMPLIED WARRANTIES OF THE PRODUCTS AND PRODUCT COMPONENTS SET FORTH IN PARAGRAPH 1 ABOVE ARE LIMITED TO THE DURATIONS OF THE RESPECTIVE WARRANTY. Some states do not allow the exclusion or limitation of incidental or consequential damages or limitations on how long an implied warranty lasts, so the above limitations may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

PROFLO is a registered trademark of Ferguson Enterprises, Inc.

© 2008 Wolseley