

Specifications

PFTPR500

Trap Primer Valve



Product Features

- Automatically primes up to six drain traps when distribution unit(s) are used
- Must install on cold water line of 1-1/2" (38mm) diameter or less
- Automatically activates with a pressure drop of 3 PSIG (20 Kpa)
- Operating range is 20 to 80 PSIG (138 to 552 Kpa)
- No adjustment or air pre-charge required
- Includes removable #60 mesh stainless steel conical filter screen
- Machined from CDA 360 corrosion-resistant (lead free) brass
- Contains no springs or diaphragms
- Metered amount of water from the floor drain trap primer is distributed to as many as six floor drain traps by means of the patented distribution unit(s)
- No air pre-charge
- Four view holes for easy inspection after installation

No. Drains	Dist. Units
1	N/A
2	PFTPDUU
3	PFTPDUU
4	PFTPDUU

Parts

Description	A (Inch)	B (Inch)	C (Inch)	D (Inch)	E (Inch)	Numbers of Drains Served
PFTPR500	4-1/8" (105)	3-1/4" (82)	7/8" (22)	1-1/4" (32)	1-1/8" (29)	6



Warranty and Codes

This PROFLO product carries a 1-year limited warranty.

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

The wetted surface contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight.

©2025 Ferguson Enterprises, LLC 0125 7317500



FERGUSON.COM/PROFLO