

# PFTPR500

## Trap Primer Valve



### Product Features

- Automatically primes up to six drain traps when distribution unit(s) are used.
- Must install on cold water line of 1-1/2" (38 mm) diameter or less.
- Automatically activates with a pressure drop of 3 PSIG (20 Kpa).
- Operating range is 20 to 80 PSIG (138 to 552 Kpa).
- No adjustment or air pre-charge required.
- Includes removable #60 mesh stainless steel conical filter screen.
- Machined from CDA 360 corrosion resistant (lead free) brass.
- Contains no springs or diaphragms.
- Metered amount of water from the floor drain trap primer is distributed to as many as six floor drain traps by means of the patented distribution unit(s).
- No air pre-charge.
- Four view holes for easy inspection after installation.

No. Drains	Dist. Units
1	N/A
2	PFTPDUU
3	PFTPDUU
4	PFTPDUU

MODEL NO.	A (INCH)	B (INCH)	C (INCH)	D (INCH)	E (INCH)	NUMBER OF DRAINS SERVED
PFTPR500	4 1/8" (105)	3 1/4" (82)	7/8" (22)	1 1/4" (32)	1 1/8" (29)	6



### Warranty and Codes

This PROFLO product carries a 1-year limited warranty.



The wetted surface contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight.



Assembled in U.S.A.



**CALIFORNIA PROPOSITION 65 WARNING**  
WARNING: This product can expose you to chemicals including Pb, Formaldehyde, Carbon Black, TNT, Acrylonitrile, Butadiene which are known to the State of California to cause cancer, and birth defects or other reproductive harm. For more information go to [www. P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).