



# WC13HP

## 1/3 HP

FOOD WASTE DISPOSER

# WC13HPWC

## 1/3 HP

WITH POWER CORD

FOOD WASTE DISPOSER

**WC13HP**

**WC13HPWC**

### Dimensions

\* Distance from bottom of sink to center line of disposer outlet. Add 1/2" when stainless steel sinks are used.  
 \*\* Length of tailpipe from center line of disposer outlet to end of tailpipe.  
 NOTE: Plumb waste line to prevent standing water in disposer motor housing.

### Submittal Sheet

- 1-year limited warranty (over-the-counter)\*
- Plastic grind chamber
- Galvanized steel grinding elements with two stainless steel 360° swivel lugs
- Stainless steel sink flange with positive seal 1-piece plastic stopper
- Overload protector manual reset
- Permanently lubricated upper and lower bearings
- Quick Lock® mounting for fast, easy installation
- Exclusive cushioned anti-splash baffle
- Dishwasher drain connection

• Westcraft WC13HPWC includes: Factory installed power cord

### Sample Specification

*Food Waste Disposer(s) shall be Westcraft WC13HP, continuous feed, with 1/3 H.P. motor, galvanized steel grinding elements with two stainless steel 360° swivel lugs.*

Westcraft WC13HPWC includes: Factory installed 3' power cord.

### 1-Year Limited Over-The-Counter Warranty

\* The complete Westcraft warranty is included in the Care & Use Booklet packed with each unit.

### Specifications

Type of Feed	Continuous
On/Off Control	Wall Switch
Motor	Single Phase
HP	1/3
Volts	120
HZ	60
RPM	1725
Amp. (Avg. Load)	5.6
Time Rating	Intermittent
Lubrication	Permanently Lubricated Upper & Lower Bearings
Shipping Weight (Approx.)	<b>WC13HP:</b> 12 lbs. 10 oz. <b>WC13HPWC:</b> 12 lbs. 14 oz.
Unit Finish	Black
Overall Height	11-1/2"
Grind Chamber Capacity	26 oz.
Motor Protection	Manual Reset Overload
Average Water Usage	Approx. 1 Gallon per Person Per Day
Average Electrical Usage	3-4 KWH per Year
Drain Connection	1-1/2" Cushioned Slip Joint
Dishwasher Drain Connection	Yes
Factory Installed Power Cord	<b>WC13HP:</b> No <b>WC13HPWC:</b> Yes

### Job Specifications

