

Model: AJA2425ZXA

Product Description

Type:	Reciprocating Compressors
Application:	LBP - Low Back Pressure
ProductDescription:	R-404A/R-407A/R-448A/R-449A/R-452A
Voltage/Frequency:	115V ~ 60Hz 100V ~ 50Hz
Version:	N/A



Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
ARI (R-407A)	115V ~ 60HZ	2277	574	667	646	3.52	.89	1.03	-23°C (-10°F)	49°C (120°F)	35°C (95°F)	4.4°C (40°F)	49°C (120°F)
ARI (R-452A)	115V ~ 60HZ	2518	635	738	690	3.65	.92	1.07	-23°C (-10°F)	49°C (120°F)	35°C (95°F)	4.4°C (40°F)	49°C (120°F)
ARI (R-448A)	115V ~ 60HZ	2494	629	731	672	3.71	.94	1.09	-23°C (-10°F)	49°C (120°F)	35°C (95°F)	4.4°C (40°F)	49°C (120°F)
ARI (R-449A)	115V ~ 60HZ	2494	629	731	672	3.71	.94	1.09	-23°C (-10°F)	49°C (120°F)	35°C (95°F)	4.4°C (40°F)	49°C (120°F)
ARI (R-404A)	115V ~ 60HZ	2450	617	718	755	3.25	.82	.95	-23°C (-10°F)	49°C (120°F)	35°C (95°F)	4.4°C (40°F)	49°C (120°F)

General

Evaporating Temp. Range:	-40°C to -12.2°C (-40°F to 10°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	50
Weight Unit of Measure:	LB
Displacement (cc):	22.632
Oil Type:	Polyolester
Viscosity (cSt):	32
Oil Charge (cc):	782

Electrical

Voltage Range (50 Hz):	90-110
Voltage Range (60 Hz):	103-127
Locked Rotor Amps (LRA):	68.4

Rated Load Amps (RLA 50 Hz):	0
Rated Load Amps (RLA 60 Hz):	7.9
Max. Continuous Current (MCC in Amps):	12.8
Motor Resistance (Ohm) - Main:	.48
Motor Resistance (Ohm) - Start:	3.06
MotorType:	CSR
Overload Type:	
Relay Type:	

Agency Approval

cURus Recognized