


## CEILING DIFFUSERS


ROUND CEILING DIFFUSERS

**MODELS: RD2S, RDAS** 

SUSTAINABLE EXTRUDED ALUMINUM

Dimensions are in inches (mm)





- A = inside diameter of diffuser throat.
- B = distance from ceiling opening to edge of diffuser face.
- C = projection of diffuser from ceiling surface.
- D = diffuser overall dimension.


DIMENSION CHART				
SIZE	Α	В	С	D
6"	6 1/8	3	3/4	12 1/8
8"	8 1/8	3 11/16	1	15 1/2
10"	10 1/8	4 3/8	1 1/4	18 7/8
12"	12 1/8	5 1/16	1 3/8	22 1/4
14"	14 1/8	5 3/4	1 9/16	25 5/8
16"	16 1/8	6 7/16	1 3/4	29
18"	18 1/8	7 1/8	1 15/16	32 3/8
20"	20 1/8	7 13/16	2 1/8	35 3/4
24"	24 1/8	9 3/16	2 1/2	42 1/2

## **DESCRIPTION:**

- Model RD-AS is an all-aluminum unit painted either aluminum or white in color. The unit provides 3/4" adjustability through utilization of a threaded mechanism. The "UP" position of the core provides vertical throw, and the "DOWN" position provides horizontal throw. The core is easily adjusted. An optional round opposed blade damper is screwdriver-operated through the face of the unit.
- 2. Model RD-2-S is an all-aluminum unit painted either aluminum or white in color. The core is fixed in either "UP" or "DOWN" position through a system of clips to stationary positions. The core is easily adjusted. An optional round opposed blade damper is screwdriveroperated through the face of the unit.

### MODEL:

# RD2S, RDAS



### $\square$ RD2S

Round ceiling diffuser with 2 position core

#### $\square$ RDAS

Round ceiling diffuser with adjustable core

### **OPTIONS:**

- 1. Finish
  - ☐ ANOD Clear Anodized
  - □ WHITE
  - ☐ MB Medium Bronze
  - □ B Black
  - Custom

PROJECT:

ENGINEER: DATE SERIES DRAWING NO.
CONTRACTOR: