

LED Flush Mount

 Pendant/ceiling semi-flush mounted • Damp location listed **PROGRESS LED**


Description:

Designed for both commercial and residential interiors, Apogee is an energy efficient, high performance LED fixture. All fixtures feature 120-277V input with standard dimming. Etched glass shade provides an even and pleasing light effect. Apogee is 3000K, 90+ CRI and meets California Title 24 - JA8 - 2016 standards and is ENERGY STAR rated and damp location listed. The Apogee Collection 21" LED Flush Mount is complimented by a Brushed Nickel finish.

Specifications:

- Brushed Nickel (-009) (plated)
- Steel Construction
- Etched Glass shade
- Semi-flush fixture convertible to hanging pendant with included hardware and instructions
- Commercial-grade construction and performance
- Features Brushed Nickel finish
- Etched glass shade provides an even and pleasing light effect
- Features 41-watt integrated LED to deliver energy savings and reduce long-term maintenance costs
- 120-277V operation, 0-10V compatible dimming
- 3000K color temperature, 90CRI
- 2550 lm, 62 Lum/Watt (delivered)
- ENERGY STAR certified.
- California JA8 certified.
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 JA8-2016

Performance:

| | |
|------------------------|---|
| Number of Modules | 1 |
| Input Power | 41w |
| Input Voltage | 120-277 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Delivered) | 2550/62 (LM-79) |
| CCT | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 58,000 (L70/TM-21) |
| FCC | FCC Title 47, Part 15, Class A |
| Min. Start Temp | -30 °C |
| Max. Operating Temp | 30°C |
| Warranty | 5 year limited warranty |
| Labels | cETLus Damp location listed ENERGY STAR® qualified Meets California Title 24 JA8-2016 |

P350071-009-30

Images:



Dimensions:

Diameter: 21"
Height: 4-1/2"

Glass
Width: 18-5/8"
Height: 3"

P350071-009-30**Dimming Notes:**

P350071 is designed to be compatible with many 0-10V controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron - NFTV

Lutron - NTFTV

Lutron - DDTV

Leviton - AWSMT-7DW

Leviton - IP710

Lithonia ISD BC

Pass & Seymour - CD4FB

Wattstopper ADF-120277

Hunt Dimming - PS-010-120V

Hunt Dimming - PS010 277V

Lightolier Controls - MP1500FAM120

Lightolier Controls - ZP600FAM120

Synergy Lighting Controls - V2000FAMU

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.