# **Line Voltage Thermostats**



#### TS521W Single Pole

• SPST - Breaks one line thermostatically

#### **TD522W Double Pole**

- Breaks one line thermostatically / one line mechanically in OFF position
- Provides positive off regardless of ambient temperature

#### **Features**

- Attractive new styling suits all decors
- Contoured for use with electric baseboard and fan forced heaters
- Rounded edges, slimline design
- Large, easy-to-read control dial
- Neutral white finish
- Each thermostat includes choice of Fahrenheit or Celsius temperature scale – just snap in desired insert
- Bimetal sensing
- Designed for superior ventilation across bimetal for optimum accuracy
- Lead wires are enclosed into switch for safety no exposed electrical contacts

### **Technical Specifications**

- Temperature range 45° to 90° F, 5° to 35° C
- Rated up to 277 volts AC
- Inductive rating up to 1/6 HP @ 120 volts, 1/3 HP @ 240 volts
- Performance rated for 16 amps
- Cycle-to-cycle accuracy of 1.8° F / 1° C





Specifications subject to change

## IELIECTRCIMCIDIE®

TO ORDER PLEASE CALL 1-800-668-6663 OR FAX 1-800-668-6665



# Includes Celcius and Fahrenheit inserts

## **Electrical Rating**

22 amps / 2640 watts @ 120 VAC

22 amps / 4576 watts @ 208 VAC

22 amps / 5280 watts @ 240 VAC

18 amps / 4986 watts @ 277 VAC

Dimplex North America Limited www.dimplex.com 1367 Industrial Road, Cambridge, Ontario, Canada, N1R 7G8

Printed in Canada LI-189R

Thermostat Sell Sheet EM 2.indd 1 11/20/06 2:50:05 PM