

RPH Series Outdoor Rated Stainless Steel Electric Infrared Heater

72



Mounting Plate (provided) on top center allows heater to be mounted parallel or angled using a standard pipe nipple and box cover (supplied by installer)

- Instant, high-intensity radiant heat, with 30° symmetric heat pattern.
- Listed for indoor spot heating and for outdoor unprotected applications.
- Specialized Ruby "Red" Quartz Lamp infrared heating element for glare reduction.
- Stainless Steel housing with Coilzak Aluminum reflector for good reflectivity & corrosion resistance.
- Heating element and mounting plate included.
- Dimensions: 24" x 5-3/8" x 4-1/2."



Manufactured in U.S.A.

Mounting Clearances	Recommended Mounting Height	
6" from ceiling 24" from vertical surface 72" from face of heater to combustible surface	RPH-208	8'-12'
	RPH-240	8'-12'

UPC# 686334	MODEL	WATTS	BTU'S	VOLTS	PHASE	AMPS	REPLACEMENT QUARTZ LAMP	WT. (LBS.)	LIST	Optional Wireguard		
884501	RPH-208-A	1600	5,461	208	1	7.7	632-1620	5	344	UPC# 686334	MODEL	LIST
884518	RPH-240-A	1600	5,461	240	1	6.7	632-1624	5		880992	RPHWG	34

MM Series "Mitey Midget" Electric Infrared Heater



Manufactured in U.S.A.


- Instant, high-intensity radiant heat, with 60° symmetric heat pattern.
- MM heaters excel as people-heaters in areas requiring a linear, compact & concentrated heat source.
- Listed for indoor industrial and commercial comfort heat applications.
- Heavy duty Aluminum extrusion with a bright Aluminum insert for maximum reflectivity.
- Anodized Aluminum housing, (0.62" thick).
- Heat Element Sold Separately.
- Dimensions: 3.750" Wide x 3.380" High.

Mounting Clearances
24" from ceiling & from vertical surface 24" from face of heater to combustible surface 36" from another heater

UPC 686334	MODEL	MAX WATTS	MAX BTU'S	VOLTS	PH	UNIT LENGTH	WT. (LBS.)	LIST	Optional Wireguards		
									UPC 686334	MODEL	LIST
444019	MM-13A	500	1707	120	1	13"	3	234	443906	MMWG-13	24
442763	MM-18A	750 / 1000	3413	208-240	1	18"	4	244	443913	MMWG-18	36
449540	MM-24A	900 / 1600	5461	208-277	1	24"	5	254	441896	MMWG-24	46
442725	MM-33A	2500	8533	480	1	33"	6	273	443920	MMWG-33	50
442039	MM-46A	3000 / 3800	12457	480-600	1	46"	7	299	442046	MMWG-46	60

All MM-13A through MM-46A models are ETL Listed for use with Quartz Lamps Only!

FFH Series Electric Utility Infrared Heater



FFH-512A

FFH-912B



Manufactured in U.S.A.

- Both FFH Series Heaters are excellent for Farrowing & Finishing applications.
- Both units feature an 8 ft. 18/3 grounded cordset to plug into any 120V service.
- Gold anodized Aluminum reflectors, with a 90° symmetrical reflector pattern.
- Compact housing design, with the following housing finish:
FFH-512A: Gold Anodized Finish
FFH-912B: Brown Enamel Finish
- Quartz Tubes Heat Element(s), Wire Guard & (2) 4' ft. Jack Chains are included.
- FFH-912B Only: Offers (2) On/Off toggle switches to operate heating elements independently.
- Listed for indoor industrial and commercial comfort heat

SIZING CHART - FFH SERIES					
MOUNTING HEIGHT	Heater Model	LENGTH	WIDTH	COVERAGE (Sq. Ft.)	WATTS / Sq. Ft.
6'	FFH-512A	7	6	42	13.1
	FFH-912B	6	7	42	21.4
7'	FFH-512A	8	7	56	9.8
	FFH-912B	7	8	56	16.1
8'	FFH-512A	9	8	72	7.6
	FFH-912B	8	9	72	12.5

UPC# 686334	MODEL	WATTS	BTU'S	VOLTS	PHASE	AMPS	REPLACEMENT QUARTZ TUBE	WT. (LBS.)	Dimensions (in.)			LIST
883894	FFH-512A	550	1877	120	1	5	671-3492	4	Length	Width	Height	
882781	FFH-912B	450/900	3072	120	1	8	671-3454	4	17	6	4	383

Mounting Clearances
3" from ceiling 24" from vertical surface 72" from floor