

## **BLAYNE**

#### **Features**

- Solid brass construction
- Brass valve bodies
- Quarter-turn washerless ceramic disc valve cartridges
- ADA compliant contemporary lever handles
- Spout assembly with integral supply hoses
- Pop-up drain with tailpiece
- 5.69" (14.5 cm) spout height at outlet
- 6.30" (16.0 cm) spout reach (c-c)
- For 8" (20.3 cm) centers Maximum 20" (50.8 cm)
- 1.2 gallons (4.5 liters) per minute maximum flow rate

### **Codes / Standards Compliance**

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- IPC
- NSF 61
- NSF 372
- ADA
- ICC/ANSI A117.1
- Energy Policy Act of 1992
- EPA Watersense
- California Energy Commission (CEC)
- $\bullet$  All applicable US Federal and State material regulations

## **Widespread Lavatory Faucet**

**FE-8700** 









#### **Colors / Finishes**

15: Polished Nickel15S: Satin Nickel - PVD26: Polished Chrome

Specified Model		
Model	Description	Colors   Finishes
FE-8700	Widespread Lavatory Faucet	☐ 15 ☐ 15S ☐ 26

## **Product Specification** Add "Length Indicator and Color / Finish" suffix to Model number, below.

The two-handle Widespread Lavatory Faucet shall be made of solid brass construction. Faucet shall incorporate a spout assembly with integral supply hoses and feature brass valve bodies with quarter-turn washerless ceramic disc valve cartridges. Faucet shall have a 1.2 gallon (4.5 liter) per minute maximum flow rate. Product shall be for 8" (20.3 cm) centers - Maximum 20" (50.8 cm). Product shall incorporate a 5.69" (14.5 cm) spout height at outlet and a 6.30" (16.0 cm) spout reach (c-c). Widespread Lavatory Faucet shall be Ferguson Model FE-8700/\_\_\_\_.

# FE-8700

## **PRODUCT DIMENSIONS** (Units are in inches)



